

10D1  
11A2




Replacement Type

TYPE 10D1

(ENGLISH BASE)

DOUBLE DIODE



CHARACTERISTICS

|                   |     |     |     |     |     |     |               |
|-------------------|-----|-----|-----|-----|-----|-----|---------------|
| Heater Voltage    | ... | ... | ... | ... | ... | ... | 13.0 volts    |
| Heater Current    | ... | ... | ... | ... | ... | ... | 0.2 amp.      |
| R.M.S. Input      | ... | ... | ... | ... | ... | ... | 50 volts max. |
| Rectified Current | ... | ... | ... | ... | ... | ... | 1.0 mA max.   |

For Diode characteristic curves refer to type 6AL5.




Replacement Type

TYPE 11A2

(ENGLISH BASE)

DOUBLE DIODE

TRIODE



CHARACTERISTICS

|                       |     |     |     |     |     |     |             |
|-----------------------|-----|-----|-----|-----|-----|-----|-------------|
| Heater Voltage        | ... | ... | ... | ... | ... | ... | 4.0 volts   |
| Heater Current        | ... | ... | ... | ... | ... | ... | 1.0 amp.    |
| Anode Voltage         | ... | ... | ... | ... | ... | ... | 200 volts   |
| Anode Current         | ... | ... | ... | ... | ... | ... | 3.0 mA      |
| Grid Voltage          | ... | ... | ... | ... | ... | ... | -2 volts    |
| Cathode Bias Resistor | ... | ... | ... | ... | ... | ... | 600 ohms    |
| Anode Impedance       | ... | ... | ... | ... | ... | ... | 18,000 ohms |
| Mutual Conductance    | ... | ... | ... | ... | ... | ... | 2.8 mA/V    |
| Amplification Factor  | ... | ... | ... | ... | ... | ... | 50          |