

10GN8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 10GN8 is the same as the 6GN8 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	10.5	volts
Warm-up time (Average)	11	sec

10HF8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 10HF8 is the same as the 6HF8 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	10.5	volts
Warm-up time (Average)	11	sec



High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 10HF8 is the same as the 6HF8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC).	10.5	volts
Current	0.45 ± 6%	amp
Warm-up time (Average).	11	sec

11CY7

Dual Triode With High-Mu Unit and Low-Mu Unit

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 11CY7 is the same as the 6CY7 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC).	11	volts
Current	0.45 ± 6%	amp
Warm-up time (Average).	11	sec



