

10P18

OUTPUT PENTODE

Indirectly heated—for series operation

GENERAL

The 10P18 is a miniature based Output Pentode having a maximum anode dissipation of 12 watts. It is intended for use in AC/DC mains powered audio output stages in equipment having series connected heater chains.

RATING

Heater Current	(amps)	I_h	0.1
Heater Voltage	(volts)	V_h	45.0
Maximum Anode Voltage	(volts)	$V_{a(max)}$	250
Maximum Screen Voltage	(volts)	$V_{g2(max)}$	200
Maximum Anode Dissipation	(watts)	$P_{a(max)}$	12
Maximum Screen Dissipation (continuous)	(watts)	$P_{g2(max)}$	1.75*
Mutual Conductance	(mA/V)	g_m	10.0†
Anode Impedance	(k Ω)	r_a	23†
Inner Amplification Factor		μ_{g1-g2}	8†
Maximum Mean Cathode Current	(mA)	$I_{k(mean)max}$	100
Maximum Heater to Cathode Voltage	(volts)	$V_{h-k(max)}$	200

* On speech and music the permissible rating at peak signal level is 6 watts.

† $V_a = V_{g2} = 170\text{ V}$; $I_a = 70\text{ mA}$; $V_{g1} = -12.5\text{ v}$.

INTER-ELECTRODE CAPACITANCES (pF)

Grid 1/Earth	C_{in}	12.0
Anode/Earth	C_{out}	6.0
Anode/Grid 1	C_{a-g1}	0.5
Grid 1/Heater	C_{g1-h}	0.25

"Earth" denotes the remaining earthy potential electrodes, heater and shields connected to cathode.

10P18

OUTPUT PENTODE

Indirectly heated—for series operation

TENTATIVE


DIMENSIONS

Maximum Overall Length	(mm)	78.5
Maximum Diameter	(mm)	22.2
Maximum Seated Height	(mm)	71.5
Approximate Nett Weight	(ozs)	$\frac{1}{2}$
Approximate Packed Weight	(ozs)	$\frac{3}{4}$

MOUNTING POSITION Unrestricted.TYPICAL OPERATION Single Valve Class A Audio Amplifier

Anode Voltage.	(volts)	V_a	160
Screen Voltage	(volts)	V_{g2}	170
Anode Current (Quiescent)	(mA)	I_a	70
Screen Current (Quiescent)	(mA)	I_{g2}	5
Grid Bias	(volts)	V_{g1}	-12.5
Power Output for 10% total Harmonic Distortion	(watts)	P_{out}	5.2
Anode Load	(ohms)	R_a	2,200
Input Swing for 10% total Harmonic Distortion (r.m.s.)	(volts)	$V_{in(rms)}$	7

These operating conditions are taken with fixed D.C. potentials.

BULB ClearBASE Noval (B9A)

Viewed from free end of pins

10P18

OUTPUT PENTODE

Indirectly heated—for series operation

TEMPERATURE

VALVE HOLDER

Ediswan Clix VH599/9, VH499/9, VH19/9 series.

CONNECTIONS

Pin 1	Internal Connection	IC
Pin 2	Grid 1	g1
Pin 3	Cathode, Grid 3	k, g3
Pin 4	Heater	h
Pin 5	Heater	h
Pin 6	Internal Connection	IC
Pin 7	Anode	a
Pin 8	Internal Connection	IC
Pin 9	Grid 2	g2


"Internal connection" indicates that the pin is connected to an electrode for the purpose of improving mechanical rigidity. The connection may not always be made to the same electrode on a given valve type, and it is essential that the corresponding valve holder socket be left unconnected.

10P18

OUTPUT PENTODE


Indirectly heated—for series operation

TENTATIVE

CHARACTERISTIC CURVES: $I_a, I_{g2}/V_{g1}$ 

10P18/UL84
OUTPUT PENTODE
 Indirectly heated—for series operation

CHARACTERISTIC CURVES : $I_a, I_{g2}/V_a$
 $V_{g2} = 100V$



10P18/UL84
OUTPUT PENTODE
 Indirectly heated—for series operation

CHARACTERISTIC CURVES: I_a/V_a
 $V_{g2} = 170V$

