

11E16
H.F. DOUBLE TETRODE
 Indirectly heated
TENTATIVE

GENERAL

The 11E16 is an internally neutralised h.f. double tetrode. It has a centre tapped heater and is intended for use as a push-pull amplifier or frequency trebler at frequencies up to 600 Mc/s.

RATING§

Heater Voltage	V_h	12.6	6.3 V
Heater Current	I_h	0.65	1.3 A
Maximum Operating Frequency	$f_{(max)}$		600 Mc/s
Maximum Permissible Temperature of hottest part of bulb			200 °C
Maximum Permissible Temperature of the base pins			180 °C

§ All limiting values are Absolute, not Design Centres.

RATING—Absolute values.

Class "C" r.f. push-pull power amplifier for c.w. telegraphy or f.m. telephony.

Maximum Anode Voltage	$V_a(max)$	600*	V
Maximum Screen Grid Voltage	$V_{g2(max)}$	300	V
Maximum Negative Control Grid Voltage	$V_{g1(max)}$	-75	V
Maximum Heater/Cathode Voltage	$V_{h-k(max)}$	100	V
Maximum Anode Dissipation	$P_a(max)$	10†	W
Maximum Screen Grid Dissipation	$P_{g2(max)}$	1.5†	W
Maximum Control Grid Dissipation	$P_{g1(max)}$	0.5†	W
Maximum Peak Cathode Current	$i_{k(pk)max}$	260†	mA

Continued

11E16

H.F. DOUBLE TETRODE

Indirectly heated

TENTATIVE

Maximum Mean Cathode Current	$I_{k(av)max}$	55† mA
Maximum Control Grid Cathode Resistance (fixed bias)	$R_{g1-k(max)}$	50+ kΩ
Maximum Control Grid Cathode Resistance (automatic bias)	$R_{g1-k(max)}$	100† kΩ
Maximum Mean Control Grid Current	$I_{g1(av)max}$	2.5† mA

* For natural cooling $V_a(max) = 600V$ up to 150 Mc/s but is limited to 250V at 600 Mc/s. For forced air cooling $V_a(max) = 600V$ up to 300 Mc/s but is limited to 400V at 600 Mc/s.

† Each section.

RATING—Absolute values.

Class "C" r.f. power amplifier with anode and screen modulation (carrier condition for use with modulation factor 1).

Maximum Anode Voltage	$V_a(max)$	600*	V
Maximum Screen Grid Voltage	$V_{g2(max)}$	300	V
Maximum Negative Control Grid Voltage	$V_{g1(max)}$	-100	V
Maximum Heater Cathode Voltage	$V_{h-k(max)}$	100	V
Maximum Anode Dissipation	$P_a(max)$	6.7†	W
Maximum Screen Grid Dissipation	$P_{g2(max)}$	1.2†	W
Maximum Control Grid Dissipation	$P_{g1(max)}$	0.5†	W
Maximum Peak Cathode Current	$I_{k(pk)max}$	400†	mA
Maximum Mean Cathode Current	$I_{k(av)max}$	50†	mA
Maximum Mean Control Grid Current	$I_{g1(av)max}$	2.5†	mA

* For natural cooling $V_a(max) = 600V$ up to 150 Mc/s but is limited to 250V at 600 Mc/s. For forced air cooling $V_a(max) = 600V$ up to 250 Mc/s but is limited to 440V at 600 Mc/s.

† Each section.

11E16
H.F. DOUBLE TETRODE
 Indirectly heated
TENTATIVE

RATING—Absolute values.

Frequency Trebler.

Maximum Anode Voltage	$V_a(\text{max})$	600	V
Maximum Screen Grid Voltage	$V_{g2}(\text{max})$	300	V
Maximum Negative Control Grid Voltage	$V_{g1}(\text{max})$	-200	V
Maximum Heater/Cathode Voltage	$V_{h-k}(\text{max})$	100	V
Maximum Anode Dissipation	$P_a(\text{max})$	10†	W
Maximum Screen Grid Dissipation	$P_{g2}(\text{max})$	1.5†	W
Maximum Control Grid Dissipation	$P_{g1}(\text{max})$	0.5†	W
Maximum Peak Cathode Current	$i_k(\text{pk})\text{max}$	275†	mA
Maximum Mean Cathode Current	$i_k(\text{av})\text{max}$	50†	mA
Maximum Control Grid/Cathode Resistance (fixed bias)	$R_{g1-k}(\text{max})$	50†	k Ω
Maximum Control Grid/Cathode Resistance (automatic bias)	$R_{g1-k}(\text{max})$	100†	k Ω
Maximum Mean Control Grid Current	$I_{g1}(\text{av})\text{max}$	2.5†	mA

† Each section.

RATING—Absolute values

Class "B" a.f. power amplifier or modulator.

Maximum Anode Voltage	$V_a(\text{max})$	600	V
Maximum Screen Grid Voltage	$V_{g2}(\text{max})$	300	V
Maximum Negative Control Grid Voltage	$V_{g1}(\text{max})$	-75	V
Maximum Heater/Cathode Voltage	$V_{h-k}(\text{max})$	100	V
Maximum Anode Dissipation	$P_a(\text{max})$	10†	W
Maximum Screen Grid Dissipation	$P_{g2}(\text{max})$	1.5†	W

Continued

11E16
H.F. DOUBLE TETRODE
 Indirectly heated
TENTATIVE

Maximum Control Grid Dissipation	Pg1(max)	0.5† W
Maximum Peak Cathode Current	ik(pk)max	120† mA
Maximum Mean Cathode Current	Ik(av)max	55† mA
Maximum Control Grid/Cathode Resistance (fixed bias)	Rg1-k(max)	50† kΩ
Maximum Control Grid/Cathode Resistance (automatic bias)	Rg1-k(max)	100† kΩ

† Each section

INTER-ELECTRODE CAPACITANCES

Anode/Grid 1 *†	ca-g1	0.04 pF
Grid 1/All other electrodes†	cg1-all	7.5 pF
Anode/All other electrodes†	ca-all	2.6 pF
Input Capacitance‡	cin	4.4 pF
Output Capacitance‡	cout	1.6 pF

* Internally neutralised for push-pull operation.

† Each section.

‡ 2 sections in push-pull.

CHARACTERISTICS†‡

Mutual Conductance	gm	3.0 mA/V
Inner Amplification Factor	μg1-g2	8.0

† Each section.

‡ At $V_a = 300V$, $V_{g2} = 250V$, $I_a = 20mA$.

DIMENSIONS


Maximum Overall Length	85 mm
Maximum Diameter	47 mm
Maximum Seated Height	73 mm
Approximate Net Weight	2 oz

11E16
H.F. DOUBLE TETRODE
 Indirectly heated
TENTATIVE

MOUNTING POSITION—Mobile operation ; vertical, base up or down. Fixed station operation ; vertical, base up or down. Horizontal ; anode pins in horizontal plane.

CAPS—Wire 2mm dia.

BASE—B7A



Viewed from free end of pins

CONNECTIONS

Pin 1	Heater	h
Pin 2	Control Grid, Section 1	g1'
Pin 3	Screen Grid	g2' g2"
Pin 4	Cathode, Beam Plates, Shield	k, bp, s
Pin 5	Heater Centre Tap	h _{ct}
Pin 6	Control Grid, Section 2	g1"
Pin 7	Heater	h
Cap No. 1	Anode, Section 1	a'
Cap No. 2	Anode, Section 2	a"