

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

FRAME-GRID CONSTRUCTION (PENTODE UNIT)

For Use in Black-and-White TV Receivers Having Low-Voltage Power Supplies. Triode Unit Useful in Sync-Separator, Sound-IF Circuits, and as a General-Purpose Voltage-Amplifier Tube. Pentode Unit Especially Suited for Video Output Service.

Electrical:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	10.9	volts
Warm-up time (Average)	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode	200 max.	volts
Heater positive with respect to cathode	200 ^a max.	volts

Direct Interelectrode Capacitances (Approx.):^b

Triode Unit:

Grid to plate.	2.8	pf
Input: G_T to $(K_P, K_P + G_3, P + IS, H)$. .	4.2	pf
Output: P_T to $(K_T, K_P + G_3, P + IS, H)$. .	2.4	pf

Pentode Unit:

Grid No.1 to plate	0.090 max.	pf
Input: G_{1P} to $(K_P + G_3, P + IS, G_2, P, H)$.	14	pf
Output: P_P to $(K_P + G_3, P + IS, G_2, P, H)$. .	4.8	pf
Triode grid to pentode plate	0.015 max.	pf
Pentode plate to triode plate.	0.17 max.	pf

Characteristics, Class A₁ Amplifier:

	Triode Unit	Pentode Unit	
Plate Supply Voltage	125	125 200 ^a	volts
Grid-No.2 Supply Voltage	—	125 125	volts
Grid-No.1 Supply	Connected to negative end of cathode resistor		
Cathode Resistor	68	82 68	ohms
Amplification Factor	46	— —	
Plate Resistance (Approx.)	4400	55000 75000	ohms
Transconductance	10400	21000 23000	μmhos
Plate Current.	15	19 22	ma
Grid-No.2 Current.	—	3.8 4	ma
Grid-No.1 Voltage (Approx.) for plate $\mu_a = 100$	-6	-4.2 -4.2	volts

^a The dc component must not exceed 100 volts.

^b without external shield.




11LQ8

Mechanical:

Operating Position Any
 Type of Cathodes Coated Unipotential
 Maximum Overall Length 2-5/8"
 Maximum Seated Length 2-3/8"
 Length, Base Seat to Bulb Top (Excluding tip) 2" $\pm$ 3/32"
 Diameter 0.750" to 0.875"
 Dimensional Outline See *General Section*
 Bulb T6-1/2
 Base Small-Button Noval 9-Pin (JEDEC No. E9-1)
 Basing Designation for BOTTOM VIEW 9DX

Pin 1 - Triode Cathode
 Pin 2 - Triode Grid
 Pin 3 - Triode Plate
 Pin 4 - Heater
 Pin 5 - Heater
 Pin 6 - Pentode Grid No. 3,
 Pentode Cathode,
 Internal Shield
 Pin 7 - Pentode Grid No. 1
 Pin 8 - Pentode Grid No. 2
 Pin 9 - Pentode Plate



AMPLIFIER — Class A₁


Maximum Ratings, Design-Maximum Values:

	Triode Unit	Pentode Unit	
Plate Voltage	300 max.	300 max.	volts
Grid-No. 2 (Screen-grid) Supply Voltage	-	300 max.	volts
Grid-No. 2 Voltage	-	See <i>Grid-No. 2 Input Rating Chart</i> at front of Receiving Tube Section	
Grid-No. 1 (Control-grid) Voltage:			
Positive-bias value	0 max.	0 max.	volts
Grid-No. 2 Input:			
For grid-No. 2 voltages up to 150 volts	-	1 max.	watt
For grid-No. 2 voltages between 150 and 300 volts	-	See <i>Grid-No. 2 Input Rating Chart</i> at front of Receiving Tube Section	
Plate Dissipation	2 max.	5 max.	watts

Maximum Circuit Values:

	Triode Unit	Pentode Unit	
Grid-No. 1-Circuit Resistance:			
For fixed-bias operation	0.5 max.	0.1 max.	megohm
For cathode-bias operation	1 max.	0.25 max.	megohm

AVERAGE CHARACTERISTICS Triode Unit




92CM-12623



11LQ8


AVERAGE PLATE CHARACTERISTICS Triode Unit



92CM-12616




AVERAGE CHARACTERISTICS Pentode Unit



92CM-12655



AVERAGE CHARACTERISTICS Pentode Unit



92CM-12654

