



6679

6679/12AT7

HIGH-MU TWIN TRIODE

9-PIN MINIATURE TYPE

For use in mobile communications equipment

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Heater arrangement	Series	Parallel	
Voltage.	12.6 $\pm$ 20%*	6.3 $\pm$ 20%*	ac or dc volts

Current:

At 12.6 volts. . .	0.15	—	amp
--------------------	------	---	-----

At 6.3 volts. . .	—	0.3	amp
-------------------	---	-----	-----

Direct Interelectrode Capacitances (Approx.):

	Without External Shield	With External Shield ^o
--	-------------------------------	---

Grid-Drive Operation:

Grid to plate (Each unit). . .	1.5	1.5	$\mu\mu\text{f}$
--------------------------------	-----	-----	------------------

Grid to cathode and heater (Each unit).	2.2	2.2	$\mu\mu\text{f}$
--	-----	-----	------------------

Plate to cathode and heater:			
Unit No.1.	0.5	1.2	$\mu\mu\text{f}$

Unit No.2.	0.4	1.5	$\mu\mu\text{f}$
--------------------	-----	-----	------------------

Cathode-Drive Operation:

Plate to cathode (Each unit) .	0.2	0.2	$\mu\mu\text{f}$
--------------------------------	-----	-----	------------------

Cathode to grid and heater (Each unit).	4.6	4.6	$\mu\mu\text{f}$
--	-----	-----	------------------

Plate to grid and heater (Each unit).	1.8	2.6	$\mu\mu\text{f}$
--	-----	-----	------------------

Heater to cathode (Each unit). .	2.4	2.4	$\mu\mu\text{f}$
----------------------------------	-----	-----	------------------

Characteristics, Class A₁ Amplifier (Each Unit):

Heater Voltage:

For series connection.	12.6	volts
--------------------------------	------	-------

For parallel connection.	6.3	volts
----------------------------------	-----	-------

Plate Supply Voltage	250	volts
--------------------------------	-----	-------

Cathode Resistor	200	ohms
----------------------------	-----	------

Amplification Factor	60	
--------------------------------	----	--

Plate Resistance (Approx.)	10900	ohms
--------------------------------------	-------	------

Transconductance	5500	μmhos
----------------------------	------	------------------

Plate Current.	10	ma
------------------------	----	----

Grid Voltage (Approx.) for plate μa = 10 .	-12	volts
---	-----	-------

Mechanical:

Operating Position	Any
------------------------------	-----

Maximum Overall Length	2-3/16"
----------------------------------	---------

Maximum Seated Length.	1-15/16"
--------------------------------	----------

Length, Base Seat to Bulb Top (Excluding tip). .	1-9/16" $\pm$ 3/32"
--	---------------------

Diameter	0.750" to 0.875"
--------------------	------------------

Dimensional Outline.	See General Section
------------------------------	---------------------

Bulb	T6-1/2
----------------	--------


Base	Small-Button Noval 9-Pin (JEDEC No.E9-1)
----------------	--



6679/12AT7

HIGH-MU TWIN TRIODE

Basing Designation for BOTTOM VIEW 9A

Pin 1—Plate of
Unit No.2Pin 2—Grid of
Unit No.2Pin 3—Cathode of
Unit No.2Pins 4 & 9—Heater of
Unit No.2Pins 5 & 9—Heater of
Unit No.1Pin 6—Plate of
Unit No.1Pin 7—Grid of
Unit No.1Pin 8—Cathode of
Unit No.1Pin 9—Heater
Mid-TapAMPLIFIER — Class A₁

Values are for Each Unit

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE. 330 max. volts

GRID VOLTAGE:

Negative-bias value. 55 max. volts

Positive-bias value. 0 max. volts

PLATE DISSIPATION. 2.8 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with
respect to cathode 100 max. voltsHeater positive with
respect to cathode 100 max. volts

* When the heater is operated from storage-battery-with-charger supply or similar supplies, the normal battery-voltage fluctuation may be as much as 35 per cent or more. Although such variation in heater voltage is permissible for short periods, reliability can be increased with improved supply-voltage regulation.

○ With external shield JEDEC No.315 connected to heater except as noted.

● With external shield JEDEC No.315 connected to ground.

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling Life Performance:

This test is performed on a sample lot of tubes from each production run. A minimum of 2000 cycles of intermittent operation is applied under the following conditions: heater volts = 15 (Series connection) cycled one minute on and one minute off, heater 135 volts positive with respect to cathode, and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Transconductance at Reduced Heater Voltage:

Average Value (Each unit). 4400 μ mhos

With heater volts = 10 (Series connection), plate supply volts = 250, and cathode resistor (ohms) bypassed = 200