

TWIN TRIODE TYPES 12AU7 AND 12AU7-A

The 12AU7 and 12AU7-A are medium-mu twin triode types of the 9-pin miniature type. Its applications include multivibrators, synchronizing amplifiers, oscillators, mixers, and industrial controls. The tube may be operated from either a 6.3-volt or 12.6-volt heater supply, and it has separate cathode terminals for each triode.

The 12AU7-A is designed to have lower microphonic noise than the 12AU7 and is thus particularly well adapted to industrial control and television horizontal oscillator applications.

ELECTRICAL:

Cathodes	Coated Unipotential		
Heater:	Series	Parallel	
Voltage	12.6	6.3	AC or DC Volts
Current	0.15	0.3	Ampere
Direct Interelectrode Capacitances (Unshielded):			
	Unit No. 1	Unit No. 2	
Grid to Plate	1.5	1.5	$\mu\mu\text{f}$
Grid to Cathode	1.6	1.6	$\mu\mu\text{f}$
Plate to Cathode	0.50	0.35	$\mu\mu\text{f}$

MECHANICAL:

Bulb	T-6-1/2
Base	Miniature 9-Pin (JEDEC E9-1)
Basing	9A
Mounting Position	Any



MAXIMUM RATINGS:

Design Maximum Values

Each Unit, Except as Noted

As

	Class A ₁ Amplifier	Vertical # Deflection Amplifier		
Plate Voltage	330	330	max.	Volts
Peak Positive Plate Voltage (Abs. Max.)	- -	1200	max.	Volts
Peak Negative Grid Voltage	- -	275	max.	Volts
Plate Dissipation:				
Each Plate	2.75	2.75*	max.	Watts
Both Plates	5.5	5.5*	max.	Watts
Cathode Current	22	22	max.	Ma.
Peak Cathode Current	- -	66	max.	Ma.
Heater-Cathode Voltage				
Heater Positive with Respect to Cathode				
D-C Component	100	100	max.	Volts
Total D-C and Peak	200	200	max.	Volts
Heater Negative with Respect to Cathode				
Total D-C and Peak	200	200	max.	Volts
Grid Circuit Resistance:				
Fixed Bias	0.25	- -	max.	Megohm
Cathode Bias	1.0	- -	max.	Megohms



MAXIMUM RATINGS:

Design Maximum Values (Each Unit, Except as Noted)

As	Vertical # Deflection Oscillator	Horizontal # Deflection Oscillator	
Plate Voltage	330	330	max. Volts
Peak Negative Grid Voltage	440	660	max. Volts
Plate Dissipation:			
Each Plate	2.75	2.75	max. Watts
Both Plates	5.5	5.5	max. Watts
Cathode Current	22	22	max. Ma.
Peak Cathode Current	66	330	max. Ma.
Heater-Cathode Voltage			
Heater Positive with Respect to Cathode			
D-C Component	100	100	max. Volts
Total D-C and Peak	200	200	max. Volts
Heater Negative with Respect to Cathode			
Total D-C and Peak	200	200	max. Volts

AMPLIFIER — CLASS A₁ Each Unit


CHARACTERISTICS:



Plate Voltage	100	250	Volts
Grid Voltage	0	-8.5	Volts
Amplification Factor	19.5	17	
Plate Resistance (Approx.)	6250	7700	Ohms
Transconductance	3100	2200	μ mhos
Plate Current	11.8	10.5	Ma.

NOTES

- # For operation in a 525-line, 30 frame system as described in, "Standards of Good Engineering Practice for Television Broadcasting Stations; Federal Communications Commission". The duty cycle of the voltage pulse must not exceed 15% of one scanning cycle.
- * Stages operating with grid-leak bias require an adequate cathode-bias resistor or other suitable means to protect the tube in the absence of excitation.

AVERAGE PLATE CHARACTERISTICS





The information contained herein is supplied without assuming responsibility for infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Westinghouse Electric Corporation.