



ELECTRONIC
INNOVATIONS
IN ACTION

TUBES

— PRODUCT INFORMATION —

Page 1 12-70

12AX3 THROUGH 12BF11

12AX3

12BE3

12BF11

12AX3 Compactron Diode. The 12AX3 is a compactron, single heater-cathode type diode, intended for service as the damping diode in the horizontal-deflection circuit of television receivers.

Except for heater characteristics, the 12AX3 is identical to the 6AX3.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC *	12.6	Volts
Heater Current •	0.6±0.04	Amperes
Heater Warm-up Time, Average ♦	11	Seconds

12BE3 Compactron Diode. The 12BE3 is a compactron, single heater-cathode type diode, intended for service as the damping diode in the horizontal deflection circuit of television receivers.

Except for heater characteristics, the 12BE3 is identical to the 6BE3.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC *	12.6	Volts
Heater Current •	0.6±0.04	Amperes
Heater Warm-up Time, Average ♦	11	Seconds

12BF11 Compactron Dissimilar Double Pentode. The 12BF11 is a compactron containing a sharp-cutoff, dual-control pentode (Section 2) and a power pentode (Section 1). The dual-control pentode is intended for use as an FM detector and the power pentode as an audio-frequency output amplifier in television receivers.

Except for heater characteristics and ratings, the 12BF11 is identical to the 6BF11.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC *	12.6	Volts
Heater Current •	0.6±0.04	Amperes
Heater Warm-up Time, average ♦	11	Seconds

GENERAL  ELECTRIC

Supersedes 12AL11 thru 12BF11 D and R Sheet dated 9-65

12AX3
12BE3
12BF11

Page 2
12-70

NOTES

- ★ Heater voltage for a bogey tube at $I_f = 0.6$ amperes.
- The equipment designer should design the equipment so that heater current is centered at the specified bogey value, with heater supply variations restricted to maintain heater current within the specified tolerance.
- ◆ The time required for the voltage across the heater to reach 80 percent of the bogey value after applying 4 times the bogey heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the bogey heater voltage divided by the bogey heater current.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an

express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

TUBE PRODUCTS DEPARTMENT
GENERAL  ELECTRIC
Owensboro, Kentucky 42301