



12E14
BEAM TETRODE
Indirectly heated
TENTATIVE

GENERAL

The 12E14 is an indirectly heated Beam Tetrode with a maximum anode dissipation of 35W. It is suitable for use in stabilised power supply units.

RATING—Absolute Values

Heater Voltage	V_h	6.3	V
Heater Current	I_h	1.6	A
Maximum Anode Voltage	$V_a(\text{max})$	800	V
Maximum Screen Voltage	$V_{g2}(\text{max})$	300	V
Maximum Control Grid Voltage	$V_{g1}(\text{max})$	-100	V
Maximum Control Grid/Screen Voltage	$V_{g1-g2}(\text{max})$	400	V
Maximum Anode Dissipation	$P_a(\text{max})$	35	W
Maximum Screen Dissipation	$P_{g2}(\text{max})$	5	W
Maximum Cathode Current	$I_k(\text{max})$	300	mA
Maximum Heater/Cathode Voltage d.c. (heater negative)	$V_{h-k}(\text{max})$	300	V


DIMENSIONS

Maximum Overall Length	106	mm
Maximum Diameter	44	mm
Maximum Seated Height	93	mm

MOUNTING POSITION—Vertical. If run horizontally then axis AB must be on a horizontal plane.

12E14
BEAM TETRODE
 Indirectly heated
TENTATIVE

BASE—I08



Viewed from free end of pins

CONNECTIONS

Pin 1	Internal Connection	IC
Pin 2	Heater	h
Pin 3	Anode	a
Pin 4	Grid 2	g2
Pin 5	Grid 1	g1
Pin 6*	Beam Plates	bp
Pin 7	Heater	h
Pin 8	Cathode	k

* Should be connected to Cathode.