



TECHNICAL DATA

Electronic Tubes

12G11

DISSIMILAR DOUBLE PENTODE

The 12G11 is a compactron containing a sharp-cutoff, dual-control pentode (Section 2) and a power pentode (Section 1). The dual-control pentode is intended for use as an FM detector and the power pentode as an audio-frequency output amplifier in television receivers.

Except for heater characteristics, the 12G11 is identical to the 6G11.

GENERAL

Electrical

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC*

12.6

Volts

Heater Current†

0.6±0.04

Amperes

Heater Warm-up Time‡

.11

Seconds

* Heater voltage for a bogey tube at $I_f = 0.6$ amperes.

+ For series heater operation, the equipment designer should design the equipment so that heater current is centered at the specified bogey value, with heater supply variations restricted to maintain heater current within the specified tolerance.

‡ The time required for the voltage across the heater to reach 80 percent of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the rated heater voltage divided by the rated heater current.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or

elements. In the absence of an express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

5/23/62 (E)

frokm JEDEC release #3531B, June 11, 1962

ETR-2196

ELECTRONIC COMPONENTS
DIVISION

GENERAL  ELECTRIC

OWENSBORO
KENTUCKY