



TUNG-SOL

BEAM PENTODE
COMPACTRON

BUTTON
12 PIN BASE E12-74
OUTLINE DRAWING
JEDEC 12-56

COATED UNIPOTENTIAL CATHODE
FOR HORIZONTAL-DEFLECTION
AMPLIFIER APPLICATIONS IN
T.V. RECEIVERS

ANY MOUNTING POSITION



BOTTOM VIEW

BASING DIAGRAM

JEDEC 12BJ

THE 12GE5 IS A BEAM-POWER PENTODE IN THE COMPACT 12 PIN, T-12 CONSTRUCTION. IT IS DESIGNED PRIMARILY FOR USE AS THE HORIZONTAL-DEFLECTION AMPLIFIER IN TELEVISION RECEIVERS.

EXCEPT FOR HEATER CHARACTERISTICS AND HEATER WARM-UP TIME, THE 12GE5 IS IDENTICAL TO THE 6GE5.

DIRECT INTERELECTRODE CAPACITANCES - APPROX.

WITHOUT EXTERNAL SHIELD*

GRID #1 TO PLATE: (G ₁ TO P)	0.34	pf
INPUT: G ₁ TO (H ⁺ K+G ₂ +B.P.)	16	pf
OUTPUT: P TO (H ⁺ K+G ₂ +B.P.)	7.0	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	12.5 VOLTS	600	MA.
HEATER SUPPLY LIMITS:			
CURRENT OPERATION		600±40	MA.
MAXIMUM HEATER-CATHODE VOLTAGE			
HEATER POSITIVE WITH RESPECT TO CATHODE			
DC COMPONENT		100	VOLTS
TOTAL DC AND PEAK		200	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK		200	VOLTS
HEATER WARM-UP TIME [□]		11	SECONDS

[□] HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 7 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

TUN-6-SOL

CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239
HORIZONTAL-DEFLECTION AMPLIFIER SERVICE •

DC PLATE-SUPPLY VOLTAGE (BOOST + DC POWER SUPPLY))	770	VOLTS
PEAK POSITIVE PULSE PLATE VOLTAGE	6500	VOLTS
PEAK NEGATIVE PULSE PLATE VOLTAGE	1500	VOLTS
GRID #2 VOLTAGE	220	VOLTS
NEGATIVE DC GRID #1 VOLTAGE	55	VOLTS
PEAK NEGATIVE GRID #1 VOLTAGE	330	VOLTS
PLATE DISSIPATION ^A	17.5	WATTS
GRID #2 DISSIPATION	3.5	WATTS
DC CATHODE CURRENT	175	MA.
PEAK CATHODE CURRENT	550	MA.
GRID #1 CIRCUIT RESISTANCE	1.0	MEGOHMS
BULB TEMPERATURE AT HOTTEST POINT	220	°C

TYPICAL OPERATING CHARACTERISTICS

AVERAGE CHARACTERISTICS

PLATE VOLTAGE	60	250	VOLTS
GRID #2 VOLTAGE	150	150	VOLTS
GRID #1 VOLTAGE	0 ^B	-22.5	VOLTS
PLATE RESISTANCE, APPROX.	---	20,000	OHMS
TRANSCONDUCTANCE	---	6600	μMHOS
PLATE CURRENT	345	75	MA.
GRID #2 CURRENT	33	2.4	MA.
GRID #1 VOLTAGE, APPROX.			
$I_b = 1.0$ MA.	---	-46	VOLTS
TRIODE AMPLIFICATION FACTOR			
G2 TIED TO PLATE, $E_b = E_{c2} = 150$ V.,			
$E_{c1} = -22.5$ V.	---	4.1	

• FOR OPERATION IN A 525-LINE, 30-FRAME SYSTEM AS DESCRIBED IN "STANDARDS OF GOOD ENGINEERING PRACTICE FOR TELEVISION BROADCAST STATIONS: FEDERAL COMMUNICATIONS COMMISSION", THE DUTY CYCLE OF THE VOLTAGE PULSE MUST NOT EXCEED 15% OF ONE SCANNING CYCLE.

A IN STAGES OPERATING WITH GRID LEAK BIAS, AN ADEQUATE CATHODE BIAS RESISTOR OR OTHER SUITABLE MEANS IS REQUIRED TO PROTECT THE TUBE IN THE ABSENCE OF EXCITATION.

B APPLIED FOR SHORT INTERVAL (TWO SECONDS MAXIMUM) SO AS NOT TO DAMAGE TUBE.