



12KP4

Description and Rating

TELEVISION PICTURE TUBE

The 12KP4 is a magnetic focus and deflection direct-view picture tube for television applications. It provides a $7\frac{1}{2} \times 10$ -inch picture. Other features of this tube are a reflective metal-backed screen which prevents ion-spot blemishes and gives improved brightness, picture contrast, and detail, and an outside conductive coating which, when grounded, serves as a filter capacitor.

GENERAL CHARACTERISTICS

ELECTRICAL:

Heater Voltage	6.3 $\pm$ 10%	Volts
Heater Current	0.6 $\pm$ 10%	Ampere
Focusing Method	Magnetic	
Deflecting Method	Magnetic	
Deflecting Angle, Approximate	54	Degrees
Phosphor - P4		
Fluorescence	White	
Persistence	Medium	
Direct Interelectrode Capacitances, Approximate		
Cathode to All Other Electrodes	5	$\mu\mu\text{f}$
Grid No.1 to All Other Electrodes	6.5	$\mu\mu\text{f}$
External Conductive Coating to Anode Capacitance	2500 Max.	$\mu\mu\text{f}$
	500 Min.	$\mu\mu\text{f}$

MECHANICAL:

Overall Length	17 $\frac{5}{8} \pm \frac{3}{8}$	Inches
Greatest Diameter of Bulb	12 $\frac{7}{16} \pm \frac{1}{8}$	Inches
Minimum Useful Screen Diameter	11	Inches
Bulb Contact	J1-21 Recessed Small-Cavity Cap	
Base	Small-Shell Duodecal 7-Pin	
Basing	12D	
Bulb Contact Alignment	Anode Contact Aligns with Pin No.3 $\pm$ 10 Degrees	

MAXIMUM RATINGS

DESIGN CENTER VALUES:

Anode Voltage	12000 Max	Volts D-C
Grid No.2 Voltage	410 Max	Volts D-C
Grid No.1 Voltage		
Negative-Bias Value	125 Max	Volts D-C
Positive-Bias Value	0 Max	Volts D-C
Positive-Peak Value	2 Max	Volts
Peak Heater-Cathode Voltage *		
Heater Negative with Respect to Cathode	140 Max	Volts D-C
Heater Positive with Respect to Cathode	140 Max	Volts D-C

* Cathode should be returned to one side or to the mid-tap of the heater transformer winding.

TYPICAL OPERATING CONDITIONS

Anode Voltage	10000	Volts D-C
Grid No.2 Voltage	250	Volts D-C
Grid No.1 Voltage **	-27 to -63	Volts D-C
Focusing Coil Current #	135 Approx.	Milliamperes D-C
Spot Position (Undelected)	20 Max	Millimeters

** Visual extinction of undeflected focused spot.

For standard focus coil or equivalent, with the combined grid No.1-bias voltage and video-signal voltage adjusted to produce a high-light brightness of 20 foot-lamberts on a $7\frac{1}{2} \times 10$ -inch picture area. Distance (D), reference line to center of air-gap, shall be $3\frac{1}{4}$ inches.

MAXIMUM CIRCUIT VALUES

Grid No.1 Circuit Resistance	1.5 Max	Megohms
------------------------------	---------	---------



GENERAL  ELECTRIC