


TUNG-SOL




HALF WAVE
HIGH VACUUM RECTIFIER

UNIPOTENTIAL CATHODE

HEATER
12.6 VOLTS 0.3 AMPERE
AC OR DC

GLASS BULB

SMALL 4 PIN BASE



4G

BOTTOM VIEW

THE TUNG-SOL 12Z3 IS DESIGNED FOR SERVICE AS A POWER RECTIFIER IN AC-DC RECEIVERS.

RATINGS

MAXIMUM DC HEATER TO CATHODE POTENTIAL	350	VOLTS
MAXIMUM PEAK INVERSE VOLTAGE	700	VOLTS
MAXIMUM STEADY-STATE PEAK PLATE CURRENT	330	MA.

OPERATING CONDITIONS AND CHARACTERISTICS

HALF WAVE RECTIFIER WITH CONDENSER INPUT TO FILTER

AC PLATE VOLTAGE (RMS)	117	150	235 ^{MAX.}	VOLTS
DC OUTPUT CURRENT ^{MAX.}	55	55	55	MA.
TOTAL EFFECTIVE PLATE SUPPLY IMPEDANCE ^{MIN.-A}	0	30	75	OHMS
TUBE VOLTAGE DROP AT 110 MA. PLATE CURRENT	17			VOLTS

^A WHEN FILTER CONDENSERS LARGER THAN 40 MFD'S ARE USED, IT MAY BE NECESSARY TO ADD ADDITIONAL PLATE SUPPLY IMPEDANCE.

FOR "INTERPRETATION OF RATINGS", REFER TO FRONT OF BOOK.

CONTINUED NEXT PAGE

