

TUBE TYPE 14L7

The 14L7 is a double diode high mu triode.

PHYSICAL SPECIFICATIONS

Cathode	Coated unipotential
Base	E8-30
Bulb	Glass
Maximum overall length	2-3/8" (60mm)
Maximum seated height	2-1/16" (53mm)
Maximum diameter	7/8" (22mm)
Mounting position	Any.

BASING CONNECTIONS 8GZ

Pin 1	Heater	Pin 5	Diode Plate No. 2
Pin 2	Triode Plate	Pin 6	Diode Plate No. 1
Pin 3	Grid	Pin 7	Cathode
Pin 4	Internal Shield	Pin 8	Heater

GENERAL ELECTRICAL DATA

Heater voltage	14	volts
Heater current	0.1	amps

ELECTRODE CAPACITANCES

Diode Plate No. 1 to Triode Grid	<0.007	μF
Diode Plate No. 2 to Triode Grid	<0.03	μF
Diode Plate to Triode Plate	<0.01	μF
Triode Grid to Cathode	2.75	μF
Triode Plate to Cathode	1.5	μF
Triode Plate to Grid	1.3	μF
Triode Grid to heater	<0.05	μF
Diode Plate No. 1 to Cathode	0.8	μF
Diode Plate No. 2 to Cathode	0.7	μF
Diode Plate No. 1 to Diode Plate No. 2	<0.3	μF
Diode Plate No. 1 to heater	<0.1	μF
Diode Plate No. 2 to heater	<0.05	μF

MAXIMUM RATINGS (Design Centre Values)Triode Section

Plate supply voltage	550	volts
Plate voltage	250	volts
Plate dissipation	1	watts
Cathode current	5.0	ma
Grid circuit resistance (with self bias)	3	megohms
Voltage between heater and cathode	150	volts
External resistance between heater and cathode	20,000	ohms.

TUBE TYPE 14L7

Diode Sections

Peak plate voltage	200	volts
Plate current	0.8	ma.

CHARACTERISTICS

Plate voltage	170	volts
Plate current	1.5	ma
Grid voltage	-1.6	volts
Transconductance	1,650	μ mhos
Plate resistance	42,000	ohms
Amplification factor	70	



