

TUNG-SOL

CATHODE RAY

THE 16RP4 AND 16RP4A ARE DIRECT-VIEW PICTURE TUBES DESIGNED FOR USE IN TELEVISION APPLICATIONS. THEY ARE IDENTICAL WITH THE FOLLOWING EXCEPTION:

16RP4A - ALUMINIZED SCREEN

THEIR COMMON FEATURES INCLUDE:

GREY FILTER FACEPLATE

UNIPOTENTIAL CATHODE	EXTERNAL CONDUCTIVE COATING
MAGNETIC FOCUS & DEFLECTION	10 1/8" X 13 1/2" RASTER SIZE
EXTERNAL SINGLE FIELD ION TRAP	RECTANGULAR GLASS CONSTRUCTION

ELECTRICAL DATA

FOCUSING METHOD		MAGNETIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.):		
HORIZONTAL	65	DEGREES
DIAGONAL	70	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	$\mu\mu\text{f}$
GRID #1 TO ALL OTHER ELECTRODES	6	$\mu\mu\text{f}$
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	1 500	$\mu\mu\text{f}$
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	750	$\mu\mu\text{f}$

OPTICAL DATA

PHOSPHOR NUMBER	NO. 4
FLUORESCENT COLOR	WHITE
PHOSPHORESCENT COLOR	WHITE
PERSISTENCE	MEDIUM
FACEPLATE LIGHT TRANSMISSION AT CENTER (APPROX.)	66 PERCENT

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC ANODE VOLTAGE	16 000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	410	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	150	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	150	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEG OHMS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE VOLTAGE	12 000	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^A	-33 to -77	VOLTS
DC FOCUSING COIL CURRENT ^B (APPROX.)	100 $\pm$ 20%	MA.
DC ION TRAP CURRENT STANDARD COIL #111 (APPROX.)	75 $\pm$ 50%	MA.

^A VISUAL EXTINCTION OF UNDEFLECTED FOCUSED SPOT.

^B FOR STANDARD FOCUS COIL #109, OR EQUIVALENT, WITH THE COMBINED GRID #1 BIAS VOLTAGE AND VIDEO SIGNAL VOLTAGE ADJUSTED TO PRODUCE A HIGHLIGHT BRIGHTNESS OF 30 FOOT LAMBERTS ON A 10 1/8" BY 13 1/2" PICTURE SIZE. DISTANCE FROM REFERENCE LINE TO CENTER OF AIR GAP ON FOCUS COIL SHALL BE 3.50 INCHES.


CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE


MECHANICAL DATA

OVERALL LENGTH	18 $\frac{3}{4}$ $\pm$ $\frac{3}{8}$	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	16 $\frac{1}{8}$ $\pm$ $\frac{1}{8}$	INCHES
WIDTH	14 $\frac{3}{4}$ $\pm$ $\frac{1}{8}$	INCHES
HEIGHT	11 $\frac{1}{2}$ $\pm$ $\frac{1}{8}$	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS:		
DIAGONAL	14 $\frac{7}{8}$	INCHES
WIDTH	13 $\frac{1}{2}$	INCHES
HEIGHT	10 $\frac{1}{8}$	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J1-21
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		12N
BULB CONTACT ALIGNMENT		
J1-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		



PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID NO. 1
 PIN 10 - GRID NO. 2



PIN 11 - CATHODE
 PIN 12 - HEATER
 ANODE CAP

BOTTOM VIEW