

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUSALUMINIZED SCREEN
90° MAGNETIC DEFLECTION

GENERAL DATA

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes. 5 pf

Grid No.1 to all other electrodes. 6 pf

External conductive coating to anode $\begin{cases} 1500 \text{ max.} \\ 1000 \text{ min.} \end{cases}$ pfHeater Current at 6.3 volts. 600 ± 30 ma

Electron Gun Type Requiring No Ion-Trap Magnet

Optical:

Phosphor (For Curves, see front of this section) .P4—Sulfide Type,
Aluminized

Faceplate, Spherical Filterglass

Light transmission (Approx.) 74%

Mechanical:

Weight (Approx.) 15 lbs

Overall Length $14\text{--}5/8" \pm 3/8"$ Neck Length. $5\text{--}1/2" \pm 3/16"$

Projected Area of Screen 149 sq. in.

External Conductive Coating:

Type Regular-Band

Contact area for grounding Near Reference Line

For Additional Information on Coatings and Dimensions:

See *Picture-Tube Dimensional-Outlines and Bulb J133 F/G*
sheets at front of this section

Cap. Recessed Small Cavity (JEDEC No.J1-21)


Bases (Alternates):

Small-Shell Duodecal 6-Pin (JEDEC Group 4, No.B6-63)

Short Small-Shell Duodecal 6-Pin (JEDEC No.B6-203)

Basing Designation for BOTTOM VIEW 12L

Pin 1—Heater
Pin 2—Grid No.1
Pin 6—Grid No.4
Pin 10—Grid No.2
Pin 11—Cathode
Pin 12—Heater



Cap—Anode
(Grid No.3,
Grid No.5,
Screen,
Collector)
C—External
Conductive
Coating

← Indicates a change.



RADIO CORPORATION OF AMERICA
Electron Tube Division

Harrison, N. J.

DATA
4-63

17BJP4

→ Maximum and Minimum Ratings, Design-Maximum Values:

*Unless otherwise specified, voltage values
are positive with respect to cathode*

ANODE VOLTAGE.	{ 17500 max. 11000 min.	volts volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value	1100 max.	volts
Negative value	550 max.	volts
GRID-No.2 VOLTAGE.	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value.	220 max.	volts
Negative bias value.	155 max.	volts
Positive bias value.	0 max.	volts
Positive peak value.	2 max.	volts
HEATER VOLTAGE	{ 6.9 max. 5.7 min.	volts volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds	450 max.	volts
After equipment warm-up period	200 max.	volts
Heater positive with respect to cathode:		
Combined AC and DC voltage	200 max.	volts
DC component	100 max.	volts

Typical Operating Conditions for Grid-Drive Service:

*Unless otherwise specified, voltage values
are positive with respect to cathode*

Anode Voltage.	14000	volts
Grid-No.4 Voltage.	-55 to +300	volts
Grid-No.2 Voltage.	300	volts
Grid-No.1 Voltage for visual extinction of focused raster	-28 to -72	volts

Maximum Circuit Value:

Grid-No.1-Circuit Resistance	1.5 max.	megohms
--	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

→ indicates a change.

