



17CDP4

KINESCOPE

Low-Voltage Electro-
static Focus
110° Magnetic Deflection

Aluminized Screen
Very Short Rectangular Glass Type
for Series Heater-String Operation

14-3/4" x 11-11/16" Screen
16-11/16" Bulb Diagonal
12-13/16" Max. Length

TENTATIVE DATA

RCA-17CDP4 is a very short, directly viewed rectangular, glass picture tube of the low-voltage electrostatic-focus and magnetic-deflection type. It has a spherical Filterglass faceplate, an aluminized screen 14-3/4" x 11-11/16" with slightly curved sides and rounded corners and a minimum projected screen area of 155 square inches.



The 17CDP4 utilizes an 8.4-volt, 450 milli-ampere heater having a controlled warm-up time to insure dependable performance in television receivers employing a series heater-string arrangement.

Designed with a 110°-diagonal deflection angle, the 17CDP4 has a very short length—a length approximately 3" shorter than types having the same size faceplate and 90° deflection. As a result, this tube establishes new concepts for cabinet styling and for the design of more compact TV receivers utilizing 17"-type picture tubes.

The 17CDP4 has a neck diameter of only 1-1/8" which not only makes possible the use of a deflect-

ing yoke having high deflection sensitivity but also permits deflection of the beam through the wide deflection angle with only slightly more power than is required to scan a tube with 90° deflection angle.

The 17CDP4 utilizes a new electron gun of the "straight" type having improved focus and a unique pre-focus lens system to maintain image sharpness over the entire screen area. This new electron gun eliminates the need for an ion-trap magnet.

Another design feature of the 17CDP4 is an integral glass-button base having straight-through leads fitted with an indexing plug. This basing arrangement eliminates any possibility of loose base-pin connections. In addition, the 17CDP4 has an external conductive bulb coating which with the internal conductive coating forms a supplementary filter capacitor.

DATA

General:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	8.4	volts
Current	0.45	amp
Warm-Up Time (Average)	11	seconds

Heater warm-up time is defined as the time required in the test circuit shown in Fig.1 for the voltage (E) across the heater terminals to increase from zero to 6.9 volts.

Direct Interelectrode Capacitances:

Grid No.1 to all other electrodes.	6	μmf
Cathode to all other electrodes.	5	μmf

External conductive coating to ultron • { 1500 max. μmf
800 min. μmf

Faceplate, Spherical Filterglass

Light transmission (approx.) 78%

Phosphor P4—Sulfide Type

Fluorescence White

Phosphorescence White

Persistence Short

Focusing Method Electrostatic

Deflection Method Magnetic

Deflection Angles (Approx.):

Diagonal	110°
Horizontal	105°
Vertical	87°

Tube Dimensions:

Overall length	12-9/16" ± 1/4"
Greatest width	15-5/8" ± 1/8"
Greatest height	12-3/4" ± 1/8"
Diagonal	16-9/16" ± 1/8"
Neck length	5-7/16" ± 1/8"

Screen Dimensions (Minimum):

Greatest width	14-3/4"
Greatest height	11-11/16"



Diagonal 15-3/4"
 Projected area 155 sq. in.
 Cap. Recessed Small Cavity (JETEC No.J1-21)
 Bulb J132-1/2 (110°)
 Base Small-Button Eightar 7-Pin Style B (JETEC No.B7-183)
 Weight (Approx.) 10 lbs
 Mounting Position. Any

GRID-DRIVE[▲] SERVICE

*Unless otherwise specified,
 voltage values are positive with respect to cathode*

Maximum and Minimum Ratings, Design-Center Values:

ULTOR [●] VOLTAGE	{16000 max. 12000 min.	volts
GRID-No.4 VOLTAGE:		volts
Positive value	1000 max.	volts
Negative value	500 max.	volts
GRID-No.2 VOLTAGE.	500 max.	volts
GRID-No.1 VOLTAGE:		volts
Negative peak value.	200 max.	volts
Negative bias value.	140 max.	volts
Positive bias value.	0 max.	volts
Positive peak value.	2 max.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	180 max.	volts
Heater positive with respect to cathode	180 max.	volts

Equipment Design Ranges:

*With any ultor voltage (E_{C5k}) between 12000 and 16000 volts
 and grid-No.2 voltage (E_{C2k}) between 200 and 500 volts*

Grid-No.4 Voltage for Focus [§]	0 to 400	volts
Grid-No.1 Voltage (E_{C1k}) for Visual Extinction of Focused Raster.	See <i>Raster-Cutoff-Range Chart</i> for Grid-Drive Service	
Grid-No.1 Video Drive from Raster Cutoff (Black Level):		
White-level value (Peak positive).	Same value as determined for E_{C1k} except video drive is a positive voltage	
Grid-No.4 Current.	-25 to +25	μamp
Grid-No.2 Current.	-15 to +15	μamp
Field Strength of Adjustable Centering Magnet*.	0 to 8	gausses

Examples of Use of Design Ranges:

<i>With ultor voltage of</i>	14000	16000	volts
<i>and grid-No.2 voltage of</i>	300	400	volts
Grid-No.4 Voltage for Focus.	0 to 400	0 to 400	volts
Grid-No.1 Voltage for Visual Extinction of Focused Raster.	-28 to -72	-36 to -94	volts
Grid-No.1 Video Drive from Raster Cutoff (Black Level):			
White-level value.	28 to 72	36 to 94	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance	1.5 max.	megohms
--	----------	---------

CATHODE-DRIVE[■] SERVICE

*Unless otherwise specified,
 voltage values are positive with respect to grid No.1*

Maximum and Minimum Ratings, Design-Center Values:

ULTOR [●] -TO-GRID-No.1 VOLTAGE.	{16000 max. 12000 min.	volts
GRID-No.4-TO-GRID-No.1 VOLTAGE:		volts
Positive value	1000 max.	volts
Negative value	500 max.	volts
GRID-No.2-TO-GRID-No.1 VOLTAGE	640 max.	volts
GRID-No.2-TO-CATHODE VOLTAGE	500 max.	volts

CATHODE-TO-GRID-No.1 VOLTAGE:

Positive peak value.	200 max.	volts
Positive bias value.	140 max.	volts
Negative bias value.	0 max.	volts
Negative peak value.	2 max.	volts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	180 max.	volts
Heater positive with respect to cathode	180 max.	volts

Equipment Design Ranges:

*With any ultor-to-grid-No.1 voltage (E_{C5g1}) between 12000
 and 16000 volts and grid-No.2-to-grid-No.1 voltage (E_{C2g1})
 between 225 and 640 volts*

Grid-No.4-to-Grid-No.1 Voltage for Focus [§]	0 to 400	volts
Cathode-to-Grid-No.1 Voltage (E_{Kg1}) for Visual Extinction of Focused Raster	See <i>Raster-Cutoff-Range Chart</i> for Cathode-Drive Service	
Cathode-to-Grid-No.1 Video Drive from Raster Cutoff (Black Level):		
White-level value.	Same value as determined for E_{Kg1} except video drive is a negative voltage	
Grid-No.4 Current.	-25 to +25	μamp
Grid-No.2 Current.	-15 to +15	μamp
Field Strength of Adjustable Centering Magnet*.	0 to 8	gausses

Examples of Use of Design Ranges:

<i>With ultor-to-grid-</i> <i>No.1 voltage of</i>	14000	16000	volts
<i>and grid-No.2-to-grid-</i> <i>No.1 voltage of</i>	300	400	volts
Grid-No.4-to-Grid- No.1 Voltage for Focus.	0 to 400	0 to 400	volts
Cathode-to-Grid-No.1 Voltage for Visual Extinction of Focused Raster	28 to 60	36 to 78	volts
Cathode-to-Grid-No.1 Video Drive from Raster Cutoff (Black Level):			
White-level value.	-28 to -60	-36 to -78	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance	1.5 max.	megohms
--	----------	---------

● The "ultor" in a cathode-ray tube is the electrode to which is applied the highest dc voltage for accelerating the electrons in the beam prior to its deflection. In the 17CDP4, the ultor function is performed by grid No.5. Since grid No.5, grid No.3, and collector are connected together within the 17CDP4, they are collectively referred to simply as "ultor" for convenience in presenting data and curves.

▲ Grid drive is the operating condition in which the video signal varies the grid-No.1 potential with respect to cathode.

§ The grid-No.4 voltage or grid-No.4-to-grid-No.1 voltage required for focus of any individual tube is independent of ultor current and will remain essentially constant for values of ultor voltage (or ultor-to-grid-No.1 voltage) or grid-No.2 voltage (or grid-No.2-to-grid-No.1 voltage) within design ranges shown for these items.

* Distance from *Reference Line* for suitable PM centering magnet should not exceed 2-1/4". Excluding extraneous fields, the center of the undeflected focused spot will fall within a circle having 5/16-inch radius concentric with the center of the tube face. It is to be noted that the earth's magnetic field can cause as much as 1/2-inch deflection of the spot from the center of the tube face.

■ Cathode drive is the operating condition in which the video signal varies the cathode potential with respect to grid No.1 and the other electrodes.



OPERATING CONSIDERATIONS

The *maximum ratings* in the tabulated data are working design-center maximums established according to the standard design-center system of rating electron tubes. Tubes so rated will give satisfactory performance in equipment designed so that these maximum ratings will not be exceeded when the equipment is operated from ac or dc power-line supplies whose normal voltage including normal variations falls within ± 10 per cent of line-center voltage value of 117 volts.

In television receivers employing series-heater strings, a resistor in series with the string of tubes will minimize voltage surges across any individual tube during starting. The resistor should preferably have a negative temperature characteristic.

X-Ray Warning. When operated at ultor voltages up to 16 kilovolts, the 17CDP4 does not produce any harmful x-ray radiation. However, because the rating of this type permits operation at voltages as high as 17.6 kilovolts (absolute maximum value), shielding of the 17CDP4 for x-ray radiation may be needed to protect against possible injury from prolonged exposure at close range whenever the operating conditions involve voltages in excess of 16 kilovolts.

The *base pins* of the 17CDP4 fit the Eightar 8-contact socket, such as Ucinite Part No. 115446, or equivalent. The design of the socket should be such that the circuit wiring cannot impress lateral strains through the socket contacts on the base pins.






Fig. 1 - Test Circuit for Determining
Heater Warm-Up Time.

Devices and arrangements shown or described herein may use patents of RCA or others. Information contained herein is furnished without responsibility by RCA for its use and without prejudice to RCA's patent rights.




92CS-9259

Fig. 2 - Raster-Cutoff Range for Type 17CDP4
in Grid-Drive Service.




92CS-9260

Fig. 3 - Raster-Cutoff Range for Type 17CDP4
in Cathode-Drive Service.



92CS-9261

Fig. 4 - Average Drive Characteristics
of Type 17CDP₄.







92CS-9262

Fig. 5 - Average Drive Characteristics
of Type 17CDP₄.



DIMENSIONAL OUTLINE

RCA-17CDP4



NOTE 1: THE PLANE THROUGH THE TUBE AXIS AND PIN No. 4 MAY VARY FROM THE PLANE THROUGH THE TUBE AXIS AND ULTOR TERMINAL BY ANGULAR TOLERANCE (MEASURED ABOUT THE TUBE AXIS) OF $\pm 30^\circ$. ULTOR TERMINAL IS ON SAME SIDE AS PIN No. 4.

NOTE 2: WITH TUBE NECK INSERTED THROUGH FLARED END OF REFERENCE-LINE GAUGE JETEC No. 126 AND WITH TUBE SEATED IN GAUGE, THE REFERENCE LINE IS DETERMINED BY THE INTERSECTION OF THE PLANE CC' OF THE GAUGE WITH THE GLASS FUNNEL.


NOTE 3: SOCKET FOR THIS BASE SHOULD NOT BE RIGIDLY MOUNTED; IT SHOULD HAVE FLEXIBLE LEADS AND BE ALLOWED TO MOVE FREELY. THE DESIGN OF THE SOCKET SHOULD BE SUCH THAT THE CIRCUITRY CANNOT IMPRESS LATERAL STRAINS THROUGH THE SOCKET CONTACTS ON THE BASE PINS. BOTTOM CIRCUMFERENCE OF BASE WAFER WILL FALL WITHIN A CIRCLE CONCENTRIC WITH BULB AXIS AND HAVING A DIAMETER OF $1\text{--}3/4$ ".

NOTE 4: EXTERNAL CONDUCTIVE COATING MUST BE GROUNDED.

NOTE 5: TO CLEAN THIS AREA, WIPE ONLY WITH SOFT DRY LINTLESS CLOTH.

NOTE 6: MEASURED $2\text{--}9/32$ " $\pm 1/32$ " FROM THE PLANE TANGENT TO THE SURFACE OF THE FACEPLATE AT THE TUBE AXIS.

NOTE 7: BULGE AT SPLICE-LINE SEAL MAY INCREASE THE INDICATED MAXIMUM VALUE FOR ENVELOPE WIDTH, DIAGONAL, AND




HEIGHT BY NOT MORE THAN $1/4$ ", BUT AT ANY POINT AROUND THE SEAL, THE BULGE WILL NOT PROTRUDE MORE THAN $1/8$ " BEYOND THE ENVELOPE SURFACE AT THE LOCATION SPECIFIED FOR DIMENSIONING THE ENVELOPE WIDTH, DIAGONAL, AND HEIGHT.



NOTE 8: THE TUBE SHOULD BE SUPPORTED ON BOTH SIDES OF THE BULGE. THE MECHANISM USED SHOULD PROVIDE CLEARANCE FOR THE MAXIMUM DIMENSIONS OF THE BULGE.




REFERENCE-LINE AND NECK-FUNNEL-CONTOUR GAUGE JETEC No 126



SMALL-BUTTON EIGHTAR BASE



SOCKET CONNECTIONS Bottom View



8HR

- PIN 1: HEATER
PIN 2: GRID No.1
PIN 3: GRID No.2
PIN 4: GRID No.4
PIN 6: GRID No.1
PIN 7: CATHODE
PIN 8: HEATER
CAP: ULTOR (Grid No.3, Grid No.5, collector)
C: EXTERNAL CONDUCTIVE COATING

NOTE 1: BASE-PIN POSITIONS ARE HELD TO TOLERANCES SUCH THAT THE BASE WILL FIT A FLAT-PLATE GAUGE HAVING A THICKNESS OF 3/8" AND EIGHT EQUALLY SPACED HOLES OF 0.0550 ± 0.0005" DIAMETER LOCATED ON A 0.6000 ± 0.0005" DIAMETER CIRCLE. THE GAUGE IS ALSO PROVIDED WITH A CENTER HOLE TO PROVIDE 0.010" DIAMETRIC CLEARANCE FOR THE LUG AND KEY. PIN FIT IN THE GAUGE SHALL BE SUCH THAT THE ENTIRE LENGTH OF PINS WILL, WITHOUT UNDUCE FORCE, ENTER INTO AND DISENGAGE FROM THE GAUGE.

NOTE 2: THIS DIMENSION AROUND THE PERIPHERY OF ANY INDIVIDUAL PIN MAY VARY WITHIN THE LIMITS SHOWN.

JETEC No.	No. OF PINS	PINS
B8-181	8-Pin	1,2,3,4,5,6,7,8
B7-182	7-Pin STYLE A	2,3,4,5,6,7,8
B7-183	7-Pin STYLE B	1,2,3,4, 6,7,8