

TUNG-SOL**CATHODE RAY**

THE 17CGP4 IS A DIRECT-VIEW PICTURE TUBE DESIGNED FOR TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

ALUMINIZED SCREEN	MAGNETIC DEFLECTION
ELECTROSTATIC FOCUS	UNIPOTENTIAL CATHODE
GRAY FILTER FACEPLATE	EXTERNAL CONDUCTIVE COATING
RECTANGULAR GLASS CONSTRUCTION	14 5/16" X 18 1/8" RASTER SIZE
DOES NOT REQUIRE ION TRAP	

ELECTRICAL DATA

FOCUSING METHOD		ELECTROSTATIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.):		
HORIZONTAL	65	DEGREES
DIAGONAL	70	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	$\mu\mu\text{f}$
GRID #1 TO ALL OTHER ELECTRODES	6	$\mu\mu\text{f}$
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	750	$\mu\mu\text{f}$
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	500	$\mu\mu\text{f}$

OPTICAL DATA

PHOSPHOR NUMBER	SULFIDE TYPE	P-4
FLUORESCENT COLOR		WHITE
PHOSPHORESCENT COLOR		WHITE
PERSISTENCE		MEDIUM
FACEPLATE TRANSMISSION AT CENTER (APPROX.):	74	PERCENT

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6 $\pm$ 10%	AMP.
MAXIMUM DC ANODE VOLTAGE	14 000	VOLTS
MAXIMUM DC GRID #4 VOLTAGE	-500 TO +1000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	500	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	180	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEGOHMS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE VOLTAGE	11 000	VOLTS
DC GRID #4 VOLTAGE	-56 TO +310	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^A	-28 TO -72	VOLTS

^A VISUAL EXTINCTION OF FOCUSED RASTER.


CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE


MECHANICAL DATA

OVERALL LENGTH	17 $\frac{3}{16}$ $\pm$ $\frac{3}{8}$	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	16 $\frac{5}{8}$ $\pm$ $\frac{1}{8}$	INCHES
WIDTH	15 $\frac{3}{8}$ $\pm$ $\frac{1}{8}$	INCHES
HEIGHT	12 $\frac{1}{4}$ $\pm$ $\frac{1}{8}$	INCHES
MIN. USEFUL SCREEN DIMENSIONS:		
DIAGONAL	15 $\frac{9}{16}$	INCHES
WIDTH	14 $\frac{5}{16}$	INCHES
HEIGHT	11 $\frac{1}{8}$	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J4-24
BASE	SMALL SHELL DUODECAL 6 PIN	B6-63
BASING		12L
BULB CONTACT ALIGNMENT		
J4-24 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		



PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID #1
 PIN 6 - GRID #4
 PIN 10 - GRID #2
 PIN 11 - CATHODE



PIN 12 - HEATER
 ANODE CAP:
 GRID NO. 3
 GRID NO. 5

BOTTOM VIEW