

Picture Tube

SHORT RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS
LOW GRID-No.2 VOLTAGE

ALUMINIZED SCREEN
110° MAGNETIC DEFLECTION
CATHODE-DRIVE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater Current at 6.3 volts.	450 ± 5%	ma
Heater Warm-Up Time (Average).	11	seconds
Direct Interelectrode Capacitances:		
Grid No.1 to all other electrodes. . .	6	μμf
Cathode to all other electrodes. . . .	5	μμf
External conductive coating to ultor .	{ 1700 max. 1200 min.	μμf
Electron Gun Type Requiring No Ion-Trap Magnet		μμf


Optical:

Faceplate.	Filterglass
Light transmission (Approx.)	77%
Phosphor (For curves, see front of this section) . P4—Sulfide Type, Aluminized	

Mechanical:

Operating Position	Any
Weight (Approx.)	10 lbs
Overall Length	12-1/8" ± 1/4"
Neck Length.	5" ± 1/8"
Projected Area of Screen	155 sq. in.
External Conductive Coating:	
Type	Regular Band
Contact area for grounding	Near Reference Line
For Additional Information on Coatings and Dimensions:	
See <i>Picture-Tube Dimensional-Outlines</i> and <i>Bulb J132-1/2 A/B</i> sheets at the front of this section	
Cap.	Recessed Small Cavity (JEDEC No.J1-21)
Base	Special 6-Pin (JEDEC No.B6-214)
Basing Designation for BOTTOM VIEW	.7FA

Pin 2—Cathode
Pin 3—Heater
Pin 4—Heater
Pin 5—Grid No.1
Pin 6—Grid No.4
Pin 7—Grid No.2



Cap—Ultor
(Grid No.3,
Grid No.5,
Collector)
C—External
Conductive
Coating



17DQP4

Maximum Ratings, *Design-Maximum Values:*

ULTOR-TO-GRID-No.1 VOLTAGE.	17600 max.	volts
GRID-No.4-TO-GRID-No.1 (FOCUSING) VOLTAGE:		
Positive value.	1100 max.	volts
Negative value.	550 max.	volts
GRID-No.2-TO-GRID-No.1 VOLTAGE.	70 max.	volts
CATHODE-TO-GRID-No.1 VOLTAGE:		
Positive bias value	150 max.	volts
Negative peak value	2 max.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period. . .	200 max.	volts
Heater positive with respect to cathode.	200 max.	volts

Typical Operating Conditions:

With ultor-to-grid-No.1 voltage of	14500	volts
and grid-No.2-to-grid-No.1 voltage of	50	volts
Grid-No.4-to-Grid-No.1 Voltage for focus	-200 to +350	volts
Cathode-to-Grid-No.1 Voltage for visual extinction of focused raster .	31 to 49	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section

