

CHARACTERISTICS

GENERAL DATA

Focusing Method	Electrostatic
Deflection Method	Magnetic
Deflection Angles (Approx.)	
Horizontal	105 Degrees
Diagonal	110 Degrees
Vertical	87 Degrees
Phosphor	Aluminized P4
Fluorescence	White
Persistence	Short to Medium
Faceplate	Gray Filter Glass
Light Transmittance (Approx.)	78 Percent

ELECTRICAL DATA

Heater Voltage	6.3 Volts	
Heater Current	0.6 Ampere	
Heater Warm-up Time ¹	11 Seconds	
Direct Interelectrode Capacitance (Approx.)		
Cathode to All Other Electrodes	5 μ f	
Grid No. 1 to All Other Electrodes	6 μ f	
External Conductive Coating to Anode ²	1500 μ f	Max.
	1000 μ f	Min.

MECHANICAL DATA

Minimum Useful Screen Dimensions	
(Maximum Assured)	14 ³ / ₄ x 11 ¹¹ / ₁₆ Inches
Minimum Useful Screen Area	155 Sq. Inches
Neck Length	4 ¹ / ₈ Inches
Overall Length	11 ¹ / ₄ Inches
Bulb	J132 ¹ / ₂ A or J132 ¹ / ₂ B
Bulb Contact (Recessed Small Cavity Cap)	J1-21
Base	B7-208
	8HR
Weight (Approx.)	10 Pounds


RATINGS

MAXIMUM RATINGS (Design Maximum Values)³

Anode Voltage	18,000 Volts	dc
Grid No. 4 Voltage (Focusing Electrode)	-550 to +1100 Volts	dc
Grid No. 2 Voltage	550 Volts	dc
Grid No. 1 Voltage		
Negative Bias Value	154 Volts	dc
Negative Peak Value	220 Volts	
Positive Bias Value	0 Volts	dc
Positive Peak Value	2 Volts	
Peak Heater-Cathode Voltage		
Heater Negative with Respect to Cathode		
During Warm-up Period		
not to Exceed 15 Seconds	450 Volts	
After Equipment Warm-up Period	200 Volts	
Heater Positive with Respect to Cathode	200 Volts	

QUICK REFERENCE DATA

Television Picture Tube
17" Direct Viewd
Rectangular Glass Type
Lightweight Tube
Spherical Faceplate
Gray Filter Glass
Aluminized Screen
Electrostatic Focus
110° Magnetic Deflection
4 1/8" Neck
No Ion Trap
External Conductive Coating



SYLVANIA
ELECTRONIC TUBES

A Division of
Sylvania Electric Products Inc.

PICTURE TUBE OPERATIONS SENECA FALLS, NEW YORK

Prepared and Released By The
TECHNICAL PUBLICATIONS SECTION
EMPORIUM, PENNSYLVANIA

JULY, 1960

PAGE 1 OF 3

File Under

TELEVISION PICTURE TUBES

TYPICAL OPERATING CONDITIONS

Grid Drive Service³

Anode Voltage	14,000 Volts	dc
Grid No. 4 Voltage for Focus	0 to 400 Volts	dc
Grid No. 2 Voltage	400 Volts	dc
Grid No. 1 Voltage Required for Cutoff ⁴	-45 to -90 Volts	dc

Cathode Drive Service⁵

Anode Voltage	14,000 Volts
Grid No. 4 Voltage for Focus	0 to 400 Volts
Grid No. 2 Voltage	450 Volts
Cathode Voltage Required for Cutoff ⁴	+46 to +85 Volts

CIRCUIT VALUES

Grid No. 1 Circuit Resistance	1.5 Megohms Max.
---	------------------

NOTES:

1. Heater warm-up time is defined as the time required for the voltage across the heater to reach 80% of the rated heater voltage after applying four (4) times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to three (3) times the rated heater voltage divided by the rated heater current.
2. External conductive coating must be grounded.
3. Voltages are positive with respect to cathode unless indicated otherwise.
4. Visual extinction of focused raster. Extinction of stationary focused spot will require that these values be increased about 5 volts.
5. Voltages are positive with respect to Grid No. 1 unless indicated otherwise.

WARNING:

X ray radiation shielding may be necessary to protect against possible danger of personal injury from prolonged exposure at close range if this tube is operated at higher than the manufacturer's Maximum Rated Anode Voltage or 16,000 volts, whichever is less.

OUTLINE




DIAGRAM NOTES:

1. Base Pin No. 4 aligns with anode contact (J1-21) within 30° .
2. Reference line is determined by plane C-C' of JEDEC No. 126 Reference Line Gauge, when the gauge is seated against the bulb.