

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
70° MAGNETIC DEFLECTION

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes.	5	pf
Grid No.1 to all other electrodes.	6	pf
External conductive coating to anode	{ 1500 max.	pf
	{ 750 min.	pf
Heater Current at 6.3 volts.	600 ± 30	ma
Electron Gun	Type Requiring	
	No Ion-Trap Magnet	

Optical:

Phosphor (For Curves, see front of this Section). P4—Sulfide Type,
 Aluminized
 Faceplate, Cylindrical Filterglass
 Light transmission (Approx.) 66%

Mechanical:


Weight (Approx.) 19 lbs
 Overall Length 19-3/16" ± 3/8"
 Neck Length. 7-1/2" ± 3/16"
 Projected Area of Screen 149 sq. in.
 External Conductive Coating:

Type Regular-Band
 Contact area for grounding Near Reference Line
 For Additional Information on Coatings and Dimensions:

See *Picture-Tube Dimensional-Outlines and Bulb J133 C/E* sheets
 at front of this section

Cap. Recessed Small Cavity (JEDEC No.J1-21)
 Base . . Small-Shell Duodecal 6-Pin (JEDEC Group 4, No.B6-63)
 Basing Designation for BOTTOM VIEW 12L

- Pin 1—Heater
- Pin 2—Grid No.1
- Pin 6—Grid No.4
- Pin 10—Grid No.2
- Pin 11—Cathode
- Pin 12—Heater



- Cap—Anode
 (Grid No.3,
 Grid No.5,
 Screen,
 Collector)
- C—External
 Conductive
 Coating

Maximum and Minimum Ratings, Design-Maximum Values:

*Unless otherwise specified, voltage values
 are positive with respect to cathode*

ANODE VOLTAGE.	17500 max.	volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value	1100 max.	volts
Negative value	550 max.	volts



17LP4B

GRID-No.2 VOLTAGE	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value	220 max.	volts
Negative bias value	155 max.	volts
Positive bias value	0 max.	volts
Positive peak value	2 max.	volts
HEATER VOLTAGE.	{	6.9 max. volts
		5.7 min. volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period		
not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period. . . .	200 max.	volts
Heater positive with respect to cathode:		
Combined AC and DC voltage.	200 max.	volts
DC component.	100 max.	volts

Typical Operating Conditions for Grid-Drive Service:

Unless otherwise specified, voltage values are positive with respect to cathode

Anode Voltage	14000	volts
Grid-No.4 Voltage	-56 to +310	volts
Grid-No.2 Voltage	300	volts
Grid-No.1 Voltage for visual extinction of focused raster.	-28 to -72	volts

Maximum Circuit Value:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

