

**VOLLWEG
BIPLAQUE
FULL WAVE**

**HOCHVAKUUM
A VIDE POUSSE
HIGH VACUUM**

Heizspannung	V_f	= 4,0 V
Tension de chauffage		
Filament voltage		
Heizstrom		ca.
Courant de chauffage	I_f	= env. 1,0 A
Filament current		appr.
Anodenwechselspannung		
Tension plaque c.a.	$V_{a \max.}$	= 2×500 V
A.C. anode voltage		
Gleichgerichteter Strom		
Courant redressé	$I_{a \max.}$	= 60 mA
Rectified current		
Max. Länge	l	= 116 mm
Longueur max.		
Overall length		
Grösster Durchmesser	d	= 53 mm
Diamètre max.		
Max. diameter		
Sockel		= A 35
Culot		
Base		
Sockelschaltung		= S III
Connexion du culot		
Base connection		

**EINWEG
MONOPLAQUE
HALFWAVE**

**HOCHVAKUUM
A VIDE POUSSE
HIGH VACUUM**

Heizspannung		
Tension de chauffage	v_f	= 4,0 V
Filament voltage		
Heizstrom		ca.
Courant de chauffage	i_f	= env. 1,0 A
Filament current		appr.
Anodenwechselspannung		
Tension plaque c.a.	$v_{a \max.}$	= 2×300 V
A.C. anode voltage		
Gleichgerichteter Strom		
Courant redressé	$i_{a \max.}$	= 100 mA
Rectified current		
Max. Länge		
Longueur max.	l	= 116 mm
Overall length		
Grösster Durchmesser		
Diamètre max.	d	= 53 mm
Max. diameter		
Sockel		
Culot		= A 35
Base		
Sockelschaltung		
Connexion du culot		= S III
Base connection		

VOLLWEG
BIPLAQUE
FULL WAVE

HOCHVAKUUM
A VIDE POUSSE
HIGH VACUUM

Heizspannung		
Tension de chauffage	v_f	= 4,0 V
Filament voltage		
Heizstrom		ca.
Courant de chauffage	i_f	= env. 1,0 A
Filament current		appr.
Anodenwechselspannung		
Tension plaque c.a.	$v_{a \max.}$	= 2×300 V
A.C. anode voltage		
Gleichgerichteter Strom		
Courant redressé	$i_{a \max.}$	= 100 mA
Rectified current		
Max. Länge		
Longueur max.	l	= 116 mm
Overall length		
Grösster Durchmesser		
Diamètre max.	d	= 53 mm
Max. diameter		
Sockel		
Culot		= A 35
Base		
Sockelschaltung		
Connexion du culot		= S III
Base connection		

**VOLLWEG
BIPLAQUE
FULL WAVE**

**HOCHVAKUUM
A VIDE POUSSE
HIGH VACUUM**

Heizspannung		
Tension de chauffage		
Filament voltage	v_f	= 4,0 V
Heizstrom		ca.
Courant de chauffage	i_f	= env. 1,0 A
Filament current		appr.
Anodenwechselspannung		
Tension plaque c.a.	$v_{a \max.}$	= 2×400 V
A.C. anode voltage		
Gleichgerichteter Strom		
Courant redressé	$i_{a \max.}$	= 75 mA
Rectified current		
Max. Länge		
Longueur max.	l	= 116 mm
Overall length		
Grösster Durchmesser		
Diamètre max.	d	= 53 mm
Max. diameter		
Sockel		
Culot		= A 35
Base		
Sockelschaltung		
Connexion du culot		= S III
Base connection		

