

**EINWEG
MONOPLAQUE
HALFWAVE**

**HOCHVAKUUM
A VIDE POUSSE
HIGH VACUUM**

Heizspannung		
Tension de chauffage	v_f	= 4,0 V
Filament voltage		
Heizstrom		ca.
Courant de chauffage	i_f	= env. 1,2 A
Filament current		appr.
Anodenwechselspannung		
Tension plaque c.a.	$v_{a\max.}$	= 700 V
A.C. anode voltage		
Gleichgerichteter Strom		
Courant redressé	$i_{a\max.}$	= 120 mA
Rectified current		
Max. Länge		
Overall length	l	= 135 mm
Longueur max.		
Grösster Durchmesser		
Diamètre max.	d	= 60 mm
Max. diameter		
Sockel		
Culot		= H 35
Base		
Sockelschaltung		
Connexion du culot		= S V
Base connection		

EINWEG
MONOPLAQUE
HALFWAVE

HOCHVAKUUM
A VIDE POUSSE
HIGH VACUUM

Heizspannung	V_f	= 4,0 V
Tension de chauffage		
Filament voltage		
Heizstrom	I_f	ca. = env. 1,2 A
Courant de chauffage		
Filament current		appr.
Anodenwechselspannung	$V_{a\max}$	= 700 V
Tension plaque c.a.		
A.C. anode voltage		
Gleichgerichteter Strom	$I_{a\max}$	= 120 mA
Courant redressé		
Rectified current		
Max. Länge	l	= 135 mm
Longueur max.		
Overall length		
Grösster Durchmesser	d	= 60 mm
Diamètre max.		
Max. diameter		
Sockel		= H 35
Culot		
Base		
Sockelschaltung		= S V
Connexion du culot		
Base connection		

