


TUNG-SOL**DOUBLE DIODE TRIODE**

MINIATURE TYPE

**GLASS BULB**


COATED UNIPOTENTIAL CATHODE

HEATER

18 VOLTS 0.10 AMP.

AC OR DC

ANY MOUNTING POSITION

**BOTTOM VIEW**MINIATURE BUTTON
7 PIN BASE

7BT

THE 18FY6 IS A MINIATURE HIGH MU TRIODE DOUBLE DIODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT HAS A 100 MA. HEATER AND IS DESIGNED FOR DETECTOR AMPLIFIER APPLICATIONS IN AC/DC TYPE RADIO RECEIVERS.

DIRECT INTERELECTRODE CAPACITANCES

	WITH SHIELD	WITHOUT SHIELD	
GRID TO PLATE	1.8	1.8	μf
INPUT	2.4	2.4	μf
OUTPUT	2	0.22	μf
GRID TO DIODE #2 PLATE (MAX.)	0.2	0.2	μf

A SHIELD #316 CONNECTED TO PIN #2.

RATINGSINTERPRETED ACCORDING TO DESIGN MAXIMUM SYSTEM^B

HEATER VOLTAGE	18	VOLTS
MAXIMUM PLATE VOLTAGE	150	VOLTS
MAXIMUM PLATE DISSIPATION	0.5	WATT
MAXIMUM POSITIVE GRID VOLTAGE	0	VOLTS
MAXIMUM DIODE PLATE CURRENT (EACH DIODE)	1.0	MA.
MAXIMUM HEATER-CATHODE VOLTAGE	100	VOLTS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS**CLASS A₁ AMPLIFIER**

HEATER VOLTAGE	18	VOLTS
HEATER CURRENT	0.10	AMP.
PLATE VOLTAGE	100	VOLTS
GRID VOLTAGE	-1	VOLTS
PLATE CURRENT	0.6	MA.
PLATE RESISTANCE	77 000	OHMS
TRANSCONDUCTANCE	1 300	μMHOS
AMPLIFICATION FACTOR	100	
AVERAGE DIODE CURRENT (EA. DIODE) WITH 10V. APPLIED ^C	2.0	MA.

^B DESIGN-MAXIMUM RATINGS ARE LIMITING VALUES OF OPERATING AND ENVIRONMENTAL CONDITIONS APPLICABLE TO A BOGEY ELECTRON DEVICE OF A SPECIFIED TYPE AS DEFINED BY ITS PUBLISHED DATA, AND SHOULD NOT BE EXCEEDED UNDER THE WORST PROBABLE CONDITIONS. THE DEVICE MANUFACTURER CHOOSES THESE VALUES TO PROVIDE ACCEPTABLE SERVICEABILITY OF THE DEVICE, TAKING RESPONSIBILITY FOR THE EFFECTS OF CHANGES IN OPERATING CONDITIONS DUE TO VARIATIONS IN DEVICE CHARACTERISTICS. THE EQUIPMENT MANUFACTURER SHOULD DESIGN SO THAT INITIALLY AND THROUGHOUT LIFE NO DESIGN-MAXIMUM VALUE FOR THE INTENDED SERVICE IS EXCEEDED WITH A BOGEY DEVICE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, SIGNAL VARIATION, AND ENVIRONMENTAL CONDITIONS.

^C TEST CONDITION ONLY.