




Obsolete Type
For Information Only
TYPE 15
(U.X. BASE)
INDIRECTLY HEATED
BATTERY R.F. PENTODE




Heater Voltage	...	2.0 volts
Heater Current	...	0.22 amp.
Anode Voltage	...	135 volts
Anode Current	...	1.85 mA
Screen (G2) Voltage	...	67.5 volts

Screen Current	...	0.3 mA
Control Grid (G1) Voltage	...	-1.5 volts
Anode Impedance	...	0.8 meg.
Mutual Conductance	...	0.7 mA/V
Max. Heater Cathode Voltage	...	22 volts




Replacement Type
TYPE 18
(U.X. BASE)
POWER PENTODE




Heater Voltage	...	14.0 volts
Heater Current	...	0.3 amp.
Anode Voltage	...	250 volts
Anode Current	...	34 mA
Screen (G2) Voltage	...	250 volts
Screen Current	...	6.5 mA

Control Grid (G1) Voltage	...	-16.5 volts
Cathode Bias Resistor	...	410 ohms
Anode Impedance	...	80,000 ohms
Mutual Conductance	...	2.5 mA/V
Optimum Load	...	7,000 ohms
Power Output	...	3.2 watts

For further information and characteristic curves refer to type 6F6G.



Obsolete Type
For Information Only
TYPE 19
(U.X. BASE)
CLASS "B" TWIN
BATTERY TRIODE



Filament Voltage	...	2.0 volts
Filament Current	...	0.26 amp.
Anode Voltage	...	135
Anode Current (Zero Signal)	...	3.4
Anode Current (Max. Signal)	...	25.0
Control Grid Voltage	...	-3
Input Power	...	0.13
Optimum Load (Anode to Anode)	...	10,000
Power Output	...	1.9

135 volts
10.0 mA
27.0 mA
0 volts
0.17 watts
10,000 ohms
2.1 watts