



1946

1946 VACUUM-GAUGE TUBE

THERMOCOUPLE TYPE


DATA**General:**

Heater, for Thermocouple:


Voltage (Approx.)	1	ac or dc volts
Current	0.070	amp
Resistance of Thermocouple	5 approx.	ohms
Maximum Overall Length (with tubulation)		6-1/4"
Maximum Diameter		1-11/16"
Bulb		T-12
Tubulation	3/8" Diameter Hard Glass,	Corning Code 772 Nonex
Mounting Position		Any
Terminal Arrangement		See Outline Drawing
Terminal Connections:		

H - Heater

TC - Thermocouple

**Calibration:**

See next page.



* MEASURED FROM BULB END TO BULB-TOP LINE AS DETERMINED BY RING GAUGE OF 1/2" I.D.

** BROWN HEATER LEAD SHOULD BE CONNECTED TO POSITIVE TERMINAL OF DC HEATER SUPPLY. 92CS-6815

JUNE 20, 1947

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

TENTATIVE DATA

1946





1946

CALIBRATION CURVES

CURVE	HEATER		
	BROWN LEAD	UNMARKED LEAD	CURRENT AMP.
1	+	-	0.070 DC
2	-	+	0.070 DC
3	±	±	0.070 RMS

GAS = DRY AIR
TO CONVERT MM TO MICRONS,
MULTIPLY VALUES BY 1000



MAR. 11, 1947

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6852