

October 1, 1961

TELEVISION PICTURE TUBE TYPE 19BFP4

92° Magnetic Deflection
Rectangular Glass
Aluminized Screen
Gray Filter Glass

6.3 Volt, 600 Ma. Heater
Electrostatic Focus

External Conductive Coating
Spherical Faceplate
No Ion Trap
12" x 15-1/8" Screen Size

ELECTRICAL:

Focusing Method	Low Voltage Electrostatic
Deflection Method	Magnetic
Deflection Angles (Approx.):	
Horizontal	80 Degrees
Vertical	65 Degrees
Diagonal	92 Degrees
Direct Interelectrode Capacitances:	
Cathode to all other electrodes, (Approx.)	5 $\mu\mu\text{f}$
Grid 1 to all other electrodes, (Approx.)	6 $\mu\mu\text{f}$
External Conductive Coating to Anode:	
Maximum	2000 $\mu\mu\text{f}$
Minimum	1000 $\mu\mu\text{f}$
Heater Current at 6.3 volts	600 $\pm$ 5% Ma.
Heater warm-up Time (Note 1)	11 Seconds

OPTICAL:

Phosphor Number	Aluminized P4
Light Transmittance at Center, Approximate	78 Percent

MECHANICAL:

Overall Length	15-1/4 $\pm$ 3/8	Inches
Greatest Dimensions of Tube:		
Diagonal	18-5/8 $\pm$ 1/8	Inches
Width	16-13/32 $\pm$ 1/8	Inches
Height	13-11/32 $\pm$ 1/8	Inches
Minimum Useful Screen Dimensions (Projected):		
Diagonal	17-9/16	Inches
Horizontal	15-1/8	Inches
Vertical	12	Inches
Area	172	Sq. Inches
Neck Length	5-1/2 $\pm$ 3/16	Inches
Bulb	J149B1	
Bulb Contact	J1-21	
Base	B6-203	
Basing	12L	
Weight	14-3/4	Pounds

RATINGS:

Design Maximum System

Unless Otherwise Specified, Voltage Values are Positive with Respect to Grid 1.

Maximum Anode Voltage	20000	Volts
Minimum Anode Voltage (Note 2)	11000	Volts
Maximum Grid 4 Voltage (Focusing Electrode)	+1100, -550	Volts
Maximum Grid 2 Voltage	700	Volts

Cathode Voltage:

Maximum Negative Value	0	Volts DC
Maximum Negative Peak Value	2	Volts
Maximum Positive Value	154	Volts DC
Maximum Positive Peak Value	220	Volts

Maximum Heater-Cathode Voltage

Heater negative with respect to cathode		
During warm-up period not to exceed		
15 seconds	450	Volts
After equipment warm-up period	200	Volts
Heater positive with respect to cathode	200	Volts

TYPICAL OPERATING CONDITIONS:

CATHODE DRIVE SERVICE:

Unless Otherwise Specified, All Voltage Values are Positive with Respect to Grid 1.


Anode Voltage	16000	Volts DC
Grid 4 Voltage (Focusing Electrode)	0 to 400	Volts DC
Grid 2 Voltage (Note 3)	400	Volts DC
Cathode Voltage for raster cutoff	34 to 79	Volts DC


LIMITING CIRCUIT VALUES:

Maximum Grid 1 Circuit Resistance	1.5	Megohms
Minimum Grids 2 & 4 Circuit Resistance (Note 4)	10000	Ohms

1. Heater warm-up time is defined as the time required for the voltage across the heater to reach 80% of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times rated heater voltage divided by rated heater current.
2. Brilliance and definition decrease with decreasing anode voltage. Operation with anode voltage less than 11000 volts is not recommended.
3. It is recommended that not less than 300 volts on grid 2 be used, as resolution is affected at lower voltages.
4. Protective resistance in the grid 2 and grid 4 (focus electrode) circuits is advisable to prevent damage to the tube.

X-RAY WARNING: Operation with voltages in excess of 16KV may require shielding to limit radiation of very soft x-rays.





CE-C1772

WESTINGHOUSE ELECTRIC CORPORATION, ELECTRONIC TUBE DIVISION, ELMIRA, NEW YORK