

PHILCO®

CATHODE RAY TUBE

DATA SHEET

TENTATIVE

19BMP4

TELEVISION

PICTURE

TUBE

DESCRIPTION

The 19BMP4 is a directly viewed, rectangular glass picture tube. The tube is electrically identical to the 19BLP4.

It incorporates a short improved electron gun requiring no ion trap magnet and which also improves edge focus quality. The tube is externally coated and features the new short integral glass button base having straight thru leads and an indexing lug.

ELECTRICAL DATA

Focusing Method	Electrostatic
Deflecting Method	Magnetic
Deflection Angle, approximate	
Horizontal	102 Degrees
Vertical	86 Degrees
Diagonal	114 Degrees
Direct Interelectrode Capacitance, approximate	
Cathode to All	4 μ f
Grid #1 to All	5 μ f
External Coating Capacitance	1300 Min. μ f
	1700 Max. μ f
Heater Voltage	6.3 Volts
Heater Current at 2.68 Volts	0.600 $\pm$.030 Amperes
Heater Warm-up Time (Note 1)	11 Seconds

OPTICAL DATA

Phosphor Number	Aluminized P4
Fluorescent Color	White
Persistence	Medium Short
Faceplate (Bonded Shield)	FP159A2
Light Transmission at Center, approximate	44 Percent

MECHANICAL DATA

Overall Length	11 $\frac{1}{16}$ $\pm$ $\frac{1}{4}$ Inches
Neck Length	4 $\frac{1}{16}$ $\pm$ $\frac{1}{16}$ Inches
Greatest Dimensions of Bulb	
Diagonal	19.856 $\pm$.094 Inches
Width	17.264 $\pm$.094 Inches
Height	14.090 $\pm$.094 Inches
Minimum Useful Screen Dimensions (maximum assured dimensions)	172 Sq. Inches
Diagonal	17 $\frac{3}{4}$ Inches
Width	15 $\frac{5}{16}$ Inches
Height	12 $\frac{1}{16}$ Inches
Bulb	J149-C1
Base	B7-208
Basing	8HR
Anode Contact	J1-21
Anode Contact Aligns with Pin #4 $\pm$ 30°	

GRID DRIVE SERVICE

Voltag es are positive with respect to cathode unless indicated otherwise.

MAXIMUM RATINGS (Design Maximum Values)

Anode Voltage (Note 2)	20,000 Max. Volts DC
Grid #4 Voltage	-550 Min. to +1100 Max. Volts DC
Grid #2 Voltage	200 Min. to 550 Max. Volts DC
Grid #1 Voltage	
Negative-Bias Value	154 Max. Volts DC
Negative-Peak Value	220 Max. Volts
Positive-Bias Value	0 Max. Volts DC
Positive-Peak Value	2 Max. Volts
Peak-Heater-Cathode Voltage	
Heater Negative with Respect to Cathode	
During Warm-up Period not to Exceed	
15 Seconds	450 Max. Volts
After Equipment Warm-up Period	200 Max. Volts
Heater Positive with Respect to Cathode	200 Max. Volts

TYPICAL OPERATING CONDITIONS

Anode Voltage	16,000 Volts DC
Grid #4 Voltage for Focus	0 to +400 Volts DC
Grid #2 Voltage	400 Volts DC
Grid #1 Voltage (Note 3)	-36 to -94 Volts DC

MAXIMUM CIRCUIT VALUES

Grid #1 Circuit Resistance	1.5 Max. Megs.
----------------------------	----------------

CATHODE DRIVE SERVICE

Voltag es are positive with respect to Grid #1 unless indicated otherwise.

MAXIMUM RATINGS (Absolute Maximum Values)

Anode Voltage (Note 2)	20,000 Max. Volts DC
Grid #4 Voltage	-400 Min. to +1250 Max. Volts DC
Grid #2 Voltage	350 Min. to 700 Max. Volts DC
Cathode Voltage	
Positive-Bias Value	154 Max. Volts DC
Positive-Peak Value	220 Max. Volts
Negative-Bias Value	0 Max. Volts DC
Negative-Peak Value	2 Max. Volts
Peak-Heater-Cathode Voltage	
Heater Negative with Respect to Cathode	
During Warm-up Period not to Exceed	
15 Seconds	450 Max. Volts
After Equipment Warm-up Period	200 Max. Volts
Heater Positive with Respect to Cathode	200 Max. Volts

from JEDEC release #3336, July 10, 1961

19BMP4

TYPICAL OPERATING CONDITIONS

Anode Voltage	16,000 Volts DC
Grid #4 Voltage for Focus	0 to 400 Volts DC
Grid #2 Voltage	400 Volts DC
Grid #1 Voltage	0 Volts DC
Cathode Voltage (Note #3)	+36 to +78 Volts DC

MAXIMUM CIRCUIT VALUES

Grid #1 Circuit Resistance	1.5 Max. Megs.
----------------------------------	----------------

NOTES

1. Heater warm-up time is defined as the time required for the voltage across the heater to reach 80% of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the rated heater voltage divided by the rated heater current.
2. Anode, Grid #3 and Grid #5 are connected together within the tube and are referred to herein as anode.
3. For visual extinction of the focused raster. For cutoff of the undeflected focus spot, the absolute value of the bias between cathode and grid will increase by about 5 volts.




DIAGRAM NOTES:

1. Reference line is determined by plane C-C' of JEDEC #126 Reference Line Gauge, when the gauge is seated against the bulb.
2. Planes perpendicular to tube axis and passing through points X, Y and Z are located as follows:

Plane tangent to crown of face to plane of X: 0.500" Nom.

Plane of X to plane of Y = .429" ± .030".

Plane of X to plane of Z = .749" ± .030".

WARNING

X-ray radiation shielding may be necessary to protect against possible danger of personal injury from prolonged exposure at close range if this tube is operated at anode voltages higher than 10,000 volts.

The information, diagrams, or any other data included herein are believed to be accurate and reliable. However, the Philco Corporation, Lansdale Division, assumes no responsibility or liability whatsoever for the application, interpretation or use made of such information, diagrams or data especially insofar as the use of said information, diagrams or data affects any patent, trademark or proprietary data rights.

PHILCO
 Famous for Quality the World Over