

October 1, 1961

## TELEVISION PICTURE TUBE TYPE 19BVP4

114° Magnetic Deflection  
Rectangular Glass  
Aluminized Screen  
Gray Filter Glass

6.3 Volt, 600 Ma. Heater  
Electrostatic Focus  
Short Neck Length

External Conductive Coating  
Spherical Faceplate  
No Ion Trap  
12" x 15-1/8" Screen Size

### ELECTRICAL:


|                                            |                           |
|--------------------------------------------|---------------------------|
| Focusing Method                            | Low Voltage Electrostatic |
| Deflection Method                          | Magnetic                  |
| Deflection Angles (Approx.):               |                           |
| Horizontal                                 | 103 Degrees               |
| Vertical                                   | 86 Degrees                |
| Diagonal                                   | 114 Degrees               |
| Direct Interelectrode Capacitances:        |                           |
| Cathode to all other electrodes, (Approx.) | 5 $\mu\mu\text{f}$        |
| Grid 1 to all other electrodes, (Approx.)  | 6 $\mu\mu\text{f}$        |
| External Conductive Coating to Anode:      |                           |
| Maximum                                    | 1500 $\mu\mu\text{f}$     |
| Minimum                                    | 1000 $\mu\mu\text{f}$     |
| Heater Current at 6.3 volts                | 600 $\pm$ 5% Ma.          |
| Heater warm-up Time (Note 1)               | 11 Seconds                |

### OPTICAL:

|                                            |               |
|--------------------------------------------|---------------|
| Phosphor Number                            | Aluminized P4 |
| Light Transmittance at Center, Approximate | 78 Percent    |

### MECHANICAL:

|                                               |                    |            |
|-----------------------------------------------|--------------------|------------|
| Overall Length                                | 11-3/4 $\pm$ 1/4   | Inches     |
| Greatest Dimensions of Tube:                  |                    |            |
| Diagonal                                      | 18-5/8 $\pm$ 1/8   | Inches     |
| Width                                         | 16-13/32 $\pm$ 1/8 | Inches     |
| Height                                        | 13-11/32 $\pm$ 1/8 | Inches     |
| Minimum Useful Screen Dimensions (Projected): |                    |            |
| Diagonal                                      | 17-9/16            | Inches     |
| Horizontal                                    | 15-1/8             | Inches     |
| Vertical                                      | 12                 | Inches     |
| Area                                          | 172                | Sq. Inches |
| Neck Length                                   | 4-1/2 $\pm$ 1/8    | Inches     |
| Bulb                                          | J149A1             |            |
| Bulb Contact                                  | J1-21              |            |
| Base                                          | B7-208             |            |
| Basing                                        | 8HR                |            |
| Weight                                        | 13-1/2             | Pounds     |



### RATINGS:

#### Design Maximum System

Unless Otherwise Specified, Voltage Values are Positive with Respect to Grid 1.

|                                             |             |          |
|---------------------------------------------|-------------|----------|
| Maximum Anode Voltage                       | 23500       | Volts    |
| Minimum Anode Voltage (Note 2)              | 12000       | Volts    |
| Maximum Grid 4 Voltage (Focusing Electrode) | +1100, -550 | Volts    |
| Maximum Grid 2 Voltage                      | 700         | Volts    |
| Cathode Voltage:                            |             |          |
| Maximum Negative Value                      | 0           | Volts DC |
| Maximum Negative Peak Value                 | 2           | Volts    |
| Maximum Positive Value                      | 154         | Volts DC |
| Maximum Positive Peak Value                 | 220         | Volts    |
| Maximum Heater-Cathode Voltage              |             |          |
| Heater negative with respect to cathode     |             |          |
| During warm-up period not to exceed         |             |          |
| 15 seconds                                  | 450         | Volts    |
| After equipment warm-up period              | 200         | Volts    |
| Heater positive with respect to cathode     | 200         | Volts    |

### TYPICAL OPERATING CONDITIONS:

#### CATHODE DRIVE SERVICE:

Unless Otherwise Specified, All Voltage Values are Positive with Respect to Grid 1.


|                                     |          |          |
|-------------------------------------|----------|----------|
| Anode Voltage                       | 20000    | Volts DC |
| Grid 4 Voltage (Focusing Electrode) | 250      | Volts DC |
| Grid 2 Voltage (Note 3)             | 500      | Volts DC |
| Cathode Voltage for raster cutoff   | 45 to 95 | Volts DC |

#### LIMITING CIRCUIT VALUES:

|                                                 |       |         |
|-------------------------------------------------|-------|---------|
| Maximum Grid 1 Circuit Resistance               | 1.5   | Megohms |
| Minimum Grids 2 & 4 Circuit Resistance (Note 4) | 10000 | Ohms    |

1. Heater warm-up time is defined as the time required for the voltage across the heater to reach 80% of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times rated heater voltage divided by rated heater current.
2. Brilliance and definition decrease with decreasing anode voltage. Operation with anode voltage less than 12000 volts is not recommended.
3. It is recommended that not less than 300 volts on Grid 2 be used, as resolution is affected at lower voltages.
4. Protective resistance in the grid 2 and grid 4 (focus electrode) circuits is advisable to prevent damage to the tube.

X-RAY WARNING: Operation with voltages in excess of 16KV may require shielding to limit radiation of very soft x-rays.



CE-C1770

NOTE 5: Anode terminal alignment with pin 4 has angular tolerance about tube axis of  $\pm 30^\circ$ .

The information contained herein is supplied without assuming responsibility for infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Westinghouse Electric Corporation.

**WESTINGHOUSE ELECTRIC CORPORATION, ELECTRONIC TUBE DIVISION, ELMIRA, NEW YORK**