

Picture Tube

SHORT RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS
LOW GRID-No.2 VOLTAGE

ALUMINIZED SCREEN
114° MAGNETIC DEFLECTION
CATHODE-DRIVE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater Current at 6.3 volts	600 $\pm$ 30	ma
Heater Warm-Up Time (Average)	11	seconds
Direct Interelectrode Capacitances:		
Grid No.1 to all other electrodes	6	μ f
Cathode to all other electrodes	5	μ f
External conductive coating to ultor.	{1500 max. 1000 min.	μ f
Electron Gun.		Type Requiring No Ion-Trap Magnet


Optical:

Faceplate	Filterglass
Light transmission (Approx.)	78%
Phosphor (For curves, see front of this section)	P4—Sulfide Type, Aluminized

Mechanical:

Operating Position.	Any
Weight (Approx.)	14 lbs
Overall Length.	11-5/8" $\pm$ 1/4"
Neck Length	4-3/8" $\pm$ 1/8"
Projected Area of Screen.	172 sq. in.
External Conductive Coating:	
Type.	Regular Band
Contact area for grounding.	Near Reference Line
For Additional Information on Coatings and Dimensions:	
See <i>Picture-Tube Dimensional-Outlines</i> and <i>Bulb J149 A</i> sheets at the front of this section	
Cap	Recessed Small Cavity (JEDEC No.J1-21)
Base.	Small-Button Neoeightar 7-Pin, Arrangement 1 (JEDEC No.B7-208)
Basing Designation for BOTTOM VIEW.	8HR

Pin 1—Heater
Pin 2—Grid No.1
Pin 3—Grid No.2
Pin 4—Grid No.4
Pin 6—Grid No.1
Pin 7—Cathode
Pin 8—Heater



Cap—Ultor
(Grid No.3,
Grid No.5,
Collector)
C—External
Conductive
Coating



19CHP4

Maximum and Minimum Ratings, Design-Maximum Values:

ULTOR-TO-GRID-No.1 VOLTAGE.	{ 20000 max. 10000 min.	volts volts
GRID-No.4-TO-GRID-No.1 (FOCUSING) VOLTAGE:		
Positive value.	1250 max.	volts
Negative value.	400 max.	volts
GRID-No.2-TO-GRID-No.1 VOLTAGE.	{ 70 max. 40 min.	volts volts
CATHODE-TO-GRID-No.1 VOLTAGE:		
Positive peak value	150 max.	volts
Positive bias value	100 max.	volts
Negative bias value	0 max.	volts
Negative peak value	2 max.	volts
HEATER VOLTAGE.	{ 6.9 max. 5.7 min.	volts volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period.	200 max.	volts
Heater positive with respect to cathode.	200 max.	volts

Typical Operating Conditions:

With ultor-to-grid-No.1 voltage of	16000	volts
and grid-No.2-to-grid-No.1 voltage of	50	volts
Grid-No.4-to-Grid-No.1 Voltage for focus .	-50 to +250	volts
Cathode-to-Grid-No.1 Voltage for visual extinction of focused raster . .	32 to 50	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section

