

19CJP4

Television Picture Tube

PHILCO CORPORATION - LANSDALE DIVISION

CATHODE RAY TUBE

DATA SHEET

Tentative

Description

The 19CJP4 is a directly viewed, rectangular glass picture tube having an aluminized screen. Other features include a relatively flat envelope, compound radius faceplate, a special internal contouring in the deflection yoke region to obtain 114° deflection with 110° components.

A short improved electron gun requiring no ion trap magnet and which also improves edge focus quality is also incorporated as well as external conductive coating and a new short integral glass button base having straight thru leads and an indexing lug.

Electrical Data

Focusing Method	Electrostatic
Deflecting Method	Magnetic
Deflection Angle, approximate	
Horizontal.	102 Degrees
Vertical.	85 Degrees
Diagonal.	114 Degrees
Direct Interelectrode Capacitance, approximate	
Cathode to All.	4 uuf
Grid #1 to All.	5 uuf
External Coating Capacitance.	1300 Min. uuf
	1700 Max. uuf
Heater Voltage.	6.3 Volts
Heater Current at 6.3 Volts	600±30 ma.
Heater Warm-up Time (Note 1)	11 Seconds

Optical Data

Phosphor Number	Aluminized P4
Fluorescent Color	White
Persistence	Medium Short
Faceplate	
Light Transmission at Center, approximate	78 Percent

Mechanical Data

Overall Length 11 5/16+1/4-3/16 Inches
 Neck Length. 4 1/8+1/16-1/8 Inches
 Greatest Dimensions of Bulb
 Diagonal 18 5/8⁺1/8 Inches
 Width. 16 13/32⁺1/8 Inches
 Height 13 11/32⁺1/8 Inches
 Minimum Useful Screen Dimensions 172 Sq. Inches
 (maximum assured dimensions)
 Diagonal 17 9/16 Inches
 Width 15 1/8 Inches
 Height 12 Inches
 Bulb J149A2
 Base B7-208
 Basing 8HR
 Anode Contact. J1-21
 Anode Contact Aligns with Pin #4[±]30°

GRID DRIVE SERVICE

Voltages are positive with respect to cathode unless indicated otherwise.

Maximum Ratings (Design Maximum Values)

Anode Voltage (Note 2) 20,000 Max. Volts DC
 Grid #4 Voltage. -550 Min. to +1100 Max. Volts DC
 Grid #2 Voltage. 200 Min. to 550 Max. Volts DC
 Grid #1 Voltage
 Negative-Bias Value. 154 Max. Volts DC
 Negative-Peak Value. 220 Max. Volts
 Positive-Bias Value. 0 Max. Volts DC
 Positive-Peak Value. 2 Max. Volts
 Peak-Heater-Cathode Voltage
 Heater Negative with Respect to Cathode
 During Warm-up Period not to Exceed
 15 Seconds 450 Max. Volts
 After Equipment Warm-up Period 200 Max. Volts
 Heater Positive with Respect to Cathode. 200 Max. Volts

Typical Operating Conditions

Anode Voltage 16,000 Volts DC
 Grid #4 Voltage for Focus. 0 to 400 Volts DC
 Grid #2 Voltage. 400 Volts DC
 Grid #1 Voltage (Note 3) -65 to -105 Volts DC

Maximum Circuit Values

Grid #1 Circuit Resistance 1.5 Max. Megs

CATHODE DRIVE SERVICE

Voltages are positive with respect to Grid #1 unless indicated otherwise.

Maximum Ratings (Absolute Maximum Values)

Anode Voltage (Note 2)	20,000 Max. Volts DC
Grid #4 Voltage	-400 Min. to +1250 Max. Volts DC
Grid #2 Voltage	.350 Min. to 700 Max. Volts DC
Cathode Voltage	
Positive-Bias Value	154 Max. Volts DC
Positive-Peak Value	220 Max. Volts
Negative-Bias Value	0 Max. Volts DC
Negative-Peak Value	2 Max. Volts
Peak-Heater-Cathode Voltage	
Heater Negative with Respect to Cathode	
During Warm-up Period not to Exceed	
15 Seconds	450 Max. Volts
After Equipment Warm-up Period	200 Max. Volts
Heater Positive with Respect to Cathode	200 Max. Volts

Typical Operating Conditions

Anode Voltage	.16,000 Volts DC
Grid #4 Voltage for Focus	0 to 400 Volts DC
Grid #2 Voltage	400 Volts DC
Grid #1 Voltage	0 Volts DC
Cathode Voltage (Note #3)	+56 to +84 Volts DC

Maximum Circuit Values

Grid #1 Circuit Resistance	1.5 Max. Megs
----------------------------	---------------

Notes

1. Heater warm-up time is defined as the time required for the voltage across the heater to reach 80% of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the rated heater voltage divided by the rated heater current.
2. Anode, Grid #3 and Grid #5 are connected together within the tube and are referred to herein as anode.
3. For visual extinction of the focused raster. For cutoff of the undeflected focus spot, the absolute value of the bias between cathode and grid will increase by about 5 volts.

The information, diagrams, or any other data included herein are believed to be accurate and reliable. However, the Philco Corporation, Lansdale Division, assumes no responsibility or liability whatsoever for the application, interpretation or use made of such information, diagrams or data especially insofar as the use of said information, diagrams or data affects any patent, trademark or proprietary data rights.