

Picture Tube

PAN-O-PLY TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

LOW-GRID-No.2 VOLTAGE
114° MAGNETIC DEFLECTION

ELECTRICAL

Direct Interelectrode Capacitances

Cathode to all other electrodes	5	pF
Grid No.1 to all other electrodes	6	pF
External conductive coating to anode. .1250 min—1750 max		pF
Heater Current at 6.3 volts.	450 ± 20	mA
Heater Warm-Up Time (Average).	11	s
Electron Gun	Type Requiring No Ion-Trap Magnet	
Focus Lens	Unipotential	

OPTICAL

Phosphor	P4—Sulfide Type, Aluminized
For curves, see front of this section	
Faceplate.	Filterglass
Light transmission at center (approx.)	48%

MECHANICAL

Weight (Approx.)	15 lb
Overall Length	11.625 ± .250 in
Neck Length.	4.375 ± .125 in
Projected Area of Screen	172 sq in
External Conductive Coating ^a	


Type	Regular-Band
Contact area for grounding	Near Reference Line
For Additional Information on Coatings and Dimensions	

See *Picture-Tube Dimensional-Outlines* and *Bulb J149F* sheets
at front of this section

Cap.	Recessed Small Cavity (JEDEC No.J1-21)
Base	Small-Button Neoeightar 7-Pin, Arrangement 1, (JEDEC No.B7-208)

TERMINAL DIAGRAM (Bottom View)

- Pin 1 - Heater
- Pin 2 - Grid No.1
- Pin 3 - Grid No.2
- Pin 4 - Grid No.4
- Pin 6 - Grid No.1
- Pin 7 - Cathode
- Pin 8 - Heater
- Cap - Anode (Grid No.3,
Grid No.5, Screen,
Collector)
- C - External Conductive
Coating



MAXIMUM AND MINIMUM RATINGS, DESIGN-MAXIMUM VALUES

*Unless otherwise specified, voltage values
are positive with respect to grid No.1*

Anode Voltage.	12000 min—23500 max	V
Grid-No.4 Voltage		
Positive value	1250 max	V
Negative value	400 max	V
Grid-No.2 Voltage.	20 min—60 max	V
Cathode Voltage		
Negative peak value.	2 max	V
Negative bias value.	0 max	V
Positive bias value.	100 max	V
Positive peak value.	150 max	V
Heater Voltage	5.7 min—6.9 max	V
Peak Heater-Cathode Voltage		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max	V
After equipment warm-up period	300 max	V
Heater positive with respect to cathode:		
Combined AC and DC voltage	200 max	V
DC component	100 max	V

TYPICAL OPERATING CONDITIONS FOR CATHODE-DRIVE SERVICE

*Unless otherwise specified, voltage values are positive
with respect to grid No.1*

Anode Voltage.	16000	V
Grid-No.4 Voltage ^b	100	V
Grid-No.2 Voltage.	30	V
Cathode Voltage.	22 to 45	V
For visual extinction of focused raster		
Field Strength of required adjustable centering magnet.	0 to 8	G

MAXIMUM CIRCUIT VALUE

Grid-No.1-Circuit Resistance	1.5 max	MΩ
--	---------	----

^a Includes implosion protection hardware.

^b The grid-No.4 voltage required for optimum focus of any individual tube will have a value anywhere between -100 and +300 volts with the combined grid-No.1 voltage and video-signal voltage adjusted to give an anode current of 100 microamperes on a 10.5-inch by 14-inch pattern from an RCA-2F21 monoscope, or equivalent.

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section

