


TUNG-SOL

DIODE

MINIATURE TYPE

FOR

USE IN PORTABLE FM RECEIVERS
AND PORTABLE HF MEASURING
EQUIPMENT




GLASS BULB

MINIATURE BUTTON
7 PIN BASE E7-1
OUTLINE DRAWING
JEDEC 5-2

COATED UNIPOTENTIAL CATHODE

ANY MOUNTING POSITION



BOTTOM VIEW

BASING DIAGRAM
JEDEC 5AP

THE 1A3 IS AN INDIRECTLY HEATED DIODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS PARTICULARLY USEFUL AS A DISCRIMINATOR TUBE IN PORTABLE FM RECEIVERS, AND IN PORTABLE HF MEASURING EQUIPMENT. THE RESONANT FREQUENCY OF THE 1A3 IS APPROXIMATELY 1000 MC/S.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

PLATE TO CATHODE (P TO K)	0.4	pf
PLATE TO HEATER (P TO H)	0.8	pf
HEATER TO CATHODE (H TO K)	0.6	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN CENTER VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	1.4	VOLTS	150	MA.
LIMITS OF APPLIED VOLTAGE			1.4±0.2	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE, DC:			140	VOLTS

RATINGS - RECTIFIER SERVICE

DESIGN CENTER VALUES - SEE EIA STANDARD RS-239

MAXIMUM PEAK INVERSE PLATE VOLTAGE,	330	VOLTS
MAXIMUM PEAK PLATE CURRENT	5	MA.
MAXIMUM DC OUTPUT CURRENT	0.5	MA.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE —

TYPICAL OPERATION WITH CONDENSER-INPUT FILTER

AC PLATE SUPPLY VOLTAGE (RMS)	117	VOLTS
FILTER INPUT CONDENSER	2	μ f
MIN. TOTAL EFFECTIVE PLATE-SUPPLY IMPEDANCE	0	OHMS

