

18106


18106 THYRODE

The 18106 is a mica-window beta counter tube designed to meet both laboratory and field requirements.

Operating voltage has been reduced to 900 volts, and photosensitivity and the effects of static charges on the window have been practically eliminated by the use of a halogen quenching gas.

The coaxial base fits Thyrode Socket No. 380 or Probe No. 263-232. Tubes are easily replaced even in water tight installations.

Resistance to vibration and shock is much greater than that of the 1867.



SYMBOL


CHARACTERISTICS

THRESHOLD VOLTAGE*	(MAX.)	825	VOLTS
PLATEAU LENGTH*	(MIN.)	150	VOLTS
PLATEAU SLOPE*	(MAX.)	10	%/100 VOLTS
(V ₀ = 800 To 1000 V)			
RECOVERY TIME		200	μSEC
BACKGROUND		40	C/M
(V ₀ = 900 V)			
LIFE		10 ¹⁰	COUNTS
(AT 6000 C/M, V ₀ = 900 V)			
ACTIVE LENGTH		1.7	INCHES
WINDOW (MICA)		2	MG/CM ²
ELECTRODE CAPACITANCE		2.5	μμF

*NEW TUBES

RATINGS

OPERATING VOLTAGE	(MIN.)	850	VOLTS
	(MAX.)	950	VOLTS
AMBIENT TEMPERATURE	(MIN.)	-55	°C
	(MAX.)	70	°C
RELATIVE HUMIDITY	(MAX.)	100	%



TUBE CHARACTERISTICS

