


TUNG-SOL

DIODE

MINIATURE TYPE



COATED UNIPOTENTIAL CATHODE


HEATER

1.4 VOLTS 0.55 AMP.

AC OR DC

ANY MOUNTING POSITION

* SOCKET TERMINALS 3 & 7 MAY BE USED AS TIE
POINTS FOR COMPONENTS AT OR NEAR FILAMENT
POTENTIAL.



BOTTOM VIEW
SMALL BUTTON
9 PIN BASE
9LX

THE 1H2 IS A MINIATURE HEATER-CATHODE TYPE DIODE DESIGNED FOR USE IN TELEVISION RECEIVERS AS THE HIGH-VOLTAGE RECTIFIER TO SUPPLY POWER TO THE ANODE OF THE TELEVISION PICTURE TUBE. THE 1H2 IS PRIMARILY INTENDED FOR USE IN FLY-BACK TYPES OF POWER SUPPLIES.

DIRECT INTERELECTRODE CAPACITANCES - APPROX.
WITHOUT EXTERNAL SHIELD

PLATE TO HEATER, CATHODE & INTERNAL SHIELD 1.0 μf

RATINGS

INTERPRETED ACCORDING TO DESIGN MAXIMUM SYSTEM
FLYBACK RECTIFIER SERVICE ^A

HEATER VOLTAGE	1.4	VOLTS
MAXIMUM PEAK INVERSE PLATE VOLTAGE		
DC COMPONENT	24 000	VOLTS
TOTAL DC AND PEAK	30 000	VOLTS
MAXIMUM STEADY-STATE PEAK PLATE CURRENT	50	MA.
MAXIMUM DC OUTPUT CURRENT	0.5	MA.

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

AVERAGE CHARACTERISTICS

TUBE VOLTAGE DROP (APPROX.)

 $I_b = 7.0 \text{ MA.}$

100 VOLTS

CONTINUED ON FOLLOWING PAGE

* INDICATES AN ADDITION.

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

NOTES

DESIGN-MAXIMUM RATINGS ARE LIMITING VALUES OF OPERATING AND ENVIRONMENTAL CONDITIONS APPLICABLE TO A BOGEY ELECTRON DEVICE OF A SPECIFIED TYPE AS DEFINED BY ITS PUBLISHED DATA, AND SHOULD NOT BE EXCEEDED UNDER THE WORST PROBABLE CONDITIONS. THE DEVICE MANUFACTURER CHOOSES THESE VALUES TO PROVIDE ACCEPTABLE SERVICEABILITY OF THE DEVICE, TAKING RESPONSIBILITY FOR THE EFFECTS OF CHANGES IN OPERATING CONDITIONS DUE TO VARIATIONS IN DEVICE CHARACTERISTICS. THE EQUIPMENT MANUFACTURER SHOULD DESIGN SO THAT INITIALLY AND THROUGHOUT LIFE NO DESIGN-MAXIMUM VALUE FOR THE INTENDED SERVICE IS EXCEEDED WITH A BOGEY DEVICE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, SIGNAL VARIATION, AND ENVIRONMENTAL CONDITIONS.

^AFOR OPERATION IN A 525-LINE, 30-FRAME SYSTEM AS DESCRIBED IN "STANDARDS OF GOOD ENGINEERING PRACTICE FOR TELEVISION BROADCAST STATIONS: FEDERAL COMMUNICATIONS COMMISSION", THE DUTY CYCLE OF THE VOLTAGE PULSE MUST NOT EXCEED 15% OF ONE SCANNING CYCLE.

THE VOLTAGES EMPLOYED IN SOME TELEVISION RECEIVERS AND OTHER HIGH-VOLTAGE EQUIPMENT ARE SUFFICIENTLY HIGH THAT HIGH-VOLTAGE RECTIFIER TUBES MAY PRODUCE SOFT X-RAYS WHICH CAN CONSTITUTE A HEALTH HAZARD UNLESS SUCH TUBES ARE ADEQUATELY SHIELDED. THE NEED FOR THIS PRECAUTION SHOULD BE CONSIDERED IN EQUIPMENT DESIGN. RELATIVELY SIMPLE SHIELDING SHOULD PROVE ADEQUATE.

