



Filament Voltage ...

Replacement Type
TYPE 1LA4E
(LOCTAL BASE)
LOW-DRAIN BATTERY
POWER PENTODE

CHARACTERISTICS

... 1.4 volts Filament Current ... 0.05 amp.
For further information refer to type 1A5G.





Filament Voltage ...

Replacement Type
TYPE 1LA6E
(LOCTAL BASE)
BATTERY HEPTODE
FREQUENCY CHANGER

CHARACTERISTICS

... 1.4 volts Filament Current ... 0.05 amp.
For further information and characteristic curves refer to type 1A7G.





Filament Voltage ...

Replacement Type
TYPE 1LH4
(LOCTAL BASE)
BATTERY SINGLE
DIODE TRIODE

CHARACTERISTICS

... 1.4 volts Filament Current ... 0.05 amp.
For further information refer to type 1H5G.




Filament Voltage ...
Filament Current ...
Anode Voltage ...
Anode Current ...
Screen (G2) Voltage ...

Replacement Type
TYPE 1LN5E
(LOCTAL BASE)
BATTERY
R.F. PENTODE

CHARACTERISTICS

... 1.4 volts Screen Current ... 0.35 mA
... 0.05 amp. Control Grid (G1) Voltage ... 0 volts
... 90 volts max. Anode Impedance ... 1.1 meg.
... 1.6 mA Mutual Conductance ... 0.8 mA/V
... 90 volts max. Mutual Conductance ... 0.01 mA/V*



* With Control Grid Voltage of -4.5 volts.