



TUNG-SOL

DIODE PENTODE
MINIATURE TYPE

GLASS BULB

HEATER

ANY MOUNTING POSITION

BOTTOM VIEW
MINIATURE BUTTON
7 PIN BASE

6BW

THE 1U5WA IS A FILAMENT TYPE, SHARP CUT-OFF, DIODE PENTODE IN THE 7 PIN MINIATURE CONSTRUCTION. ITS PRINCIPAL APPLICATION IS AS A DIODE DETECTOR, AVC RECTIFIER, AUDIO FREQUENCY AMPLIFIER IN PORTABLE RECEIVERS. THE 1U5WA IS PARTICULARLY USEFUL IN DETECTOR AMPLIFIER CIRCUITS WHERE ITS LOW MICROPHONIC NOISE AND VIBRATION OUTPUT ARE ESSENTIAL FOR SPECIALIZED MILITARY ELECTRONIC EQUIPMENT.

RATINGS

MECHANICAL

MAXIMUM IMPACT ACCELERATION (SHOCK TEST - NOTE 2)	450	G
MAXIMUM VIBRATIONAL ACCELERATION (96 HR. FATIGUE TEST - NOTE 3)	2.5	G

RATINGS

AND NORMAL OPERATION

MIL-E-1 SYMBOL	DES. MIN.	DES. TIONS NOTE 5	NORM. TEST CONDI- TION NOTE 4	NORM. OPER- ATION MAX.	DES. MAX.	MIL-E-1 UNITS
HEATER VOLTAGE (NOTE 6)	Ef: 1.00	1.25	1.25	1.50		Vdc
PLATE VOLTAGE (NOTE 7)	Eb: ---	67.5	67.5	100		Vdc
GRID VOLTAGE	Ec1: ---	0	0	0		Vdc
GRID VOLTAGE #2 (NOTE 7)	Ec2: ---	67.5	67.5	100		Vdc
PLATE DISSIPATION	Pp: ---	---	---	0.13		WATTS
GRID #2 DISSIPATION	Pg2: ---	---	---	0.035		WATTS
GRID RESISTANCE	Rg(1): ---	---	---	2.0		MEG.
TRANSCONDUCTANCE	Sm: ---	---	650	---		μMHOS
PLATE CURRENT	lb1: ---	---	1.6	---		mAcd
CATHODE CURRENT	lk: ---	---	---	5.0		mAcd
DIODE CURRENT	lib: ---	---	---	250		μAdc

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL¹

TEST	AQL %	MIL-E-1 SYMBOL	MIN.	LAL	BOG	UAL	MAX	ALD	MIL-E-1 UNITS
MEASUREMENTS ACCEPTANCE									
TESTS PART 1									
COMBINED AQL=1.0% EXCLUDING MECH. AND INOPERATIVES.									
GRID CURRENT (1):									
Eb=Ecc2=90Vdc;									
Ec1=2.5 Vdc	0.65	Ic1:	0	---	---	---	-0.5	---	μ Adc
PLATE CURRENT (1):	0.65	Ib1:	1.05	---	---	---	2.15	---	mAdc
SCREEN GRID CURRENT:	0.65	Ic(2):	0.24	---	---	---	0.56	---	mAdc
TRANSCONDUCTANCE (1):									
Ef=1.0 Vdc	0.65	Sm(1):	380	---	---	---	775	---	μ MHOS
AC AMPLIFICATION:									
Ebb=Ecc2=45 Vdc;									
Rg2=2.0 MEG; Rg1=									
10 MEG.; Rp=0.5 MEG.;									
Esig=0.2 Vac; 0.1 μ f									
BETWEEN G2 &-F	0.65	Ep:	6.5	---	---	---	---	---	Vac
EMISSION (DIODE)									
Ejb=10 Vdc	0.65	Lis:	0.5	---	---	---	---	---	mAdc
NOISE AND MICROPHONICS:									
Ebb=Ecc2=135 Vdc;									
Ecal=10.0 mVac; Rp=									
1.0 MEG.; Cg2=0.1 μ f;									
Ec1=0; Rp OF DIODE =									
2 MEG. TO GROUND.									
COUPLE PLATE OF									
DIODE TO G1 THROUGH									
A 0.1 μ f CAPACITOR;									
Rg1=1.5 MEG.; Rg2=0.1 μ f									
(NOTE 9, 10)	0.65	---	---	---	---	---	---	---	---
CONTINUITY AND SHORTS:									
(INOPERATIVES)	0.4	---	---	---	---	---	---	---	---
MECHANICAL:									
ENVELOPE OUTLINE									
(6-2)	---	---	---	---	---	---	---	---	---
MEASUREMENTS ACCEPTANCE									
TESTS, PART 2									
INSULATION OF ELEC-									
TRODES:									
g1-all=100 Vdc		Rg-all:	100	---	---	---	---	---	MEG.
p-all=100 Vdc	4.0	Rp-all:	100	---	---	---	---	---	MEG.
TRANSCONDUCTANCE (2):	6.5	Sm:	525	---	---	---	775	---	μ MHOS
FILAMENT CURRENT:	6.5	If:	44	---	---	---	56	---	mA
VIBRATION (1):									
Rp=10,000 OHMS; F=									
40 cps; G=15	6.5	Ep(1):	---	---	---	---	10	---	mVac
VIBRATION (2):									
F=50 cps-3500 cps;									
Rp=10,000 OHMS									
(NOTE 8)	6.5	Ep(2):	---	---	---	---	25	---	mVac

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS¹ - cont'd.

TEST	AQL %	MIL-E-1 SYMBOL	MIN	LAL	BOG	UAL	MAX	ALD	MIL-E-1 UNITS
DEGRADATION RATE ACCEPTANCE TESTS	COMBINED AQL = 1.0% EXCLUDING MECH. AND INOPERATIVES								
SHOCK: HAMMER ANGLE=30° (NOTE 2)	---	---	---	---	---	---	---	---	---
FATIGUE: G=2.5; F=25cps MIN., 60 cps MAX., FIXED FREQUENCY (NOTE 3)	6.5	---	---	---	---	---	---	---	---
POST SHOCK AND FATIGUE TEST END POINTS:									
TRANSCONDUCTANCE (2):	---	Sm:	450	---	---	---	---	---	μMHOS
VIBRATION (1):	---	Ep:	---	---	---	---	15	---	mVac
DIODE EMISSION	---	Iis:	0.2	---	---	---	---	---	mAdc
MINIATURE TUBE BASE STRAIN:	---	---	---	---	---	---	---	---	---
GLASS STRAIN (THERMAL SHOCK):	2.5	---	---	---	---	---	---	---	---
		ALLOW. DEF. PER CHARAC.							
TEST	1st SAMP.	COMB. SAMP.	AQL %	MIL-E-1 SYMBOL	MIN		MAX.		MIL-E-1 UNITS
ACCEPTANCE LIFE TESTS									
INTERMITTENT LIFE TEST:									
Ef=1.25 Vdc OR Vac WITH EQUIVALENT BIAS, GROUP A	---	---	---	t:	500	---	---	---	HOURS
INTERMITTENT LIFE TEST END POINTS:									
TRANSCONDUCTANCE (2)	---	---	---	Sm(2):	450	---	---	---	μMHOS
OR AC AMPLIFICATION	---	---	---	Ep:	5.0	---	---	---	Vac
EMISSION (DIODE)	---	---	---	Iis:	0.2	---	---	---	mAdc

NOTES

1. CHARACTERISTICS, QUALITY CONTROL PROCEDURES, AND INSPECTION LEVELS ARE MADE ACCORDING TO THE APPROPRIATE PARAGRAPH OF MIL-E-1, AND MIL-STD-105A.
2. TEST CONDITIONS AND ACCEPTANCE CRITERIA PER SHOCK TEST PROCEDURES OF MIL-E-1 BASIC SPECIFICATIONS.
3. TEST CONDITIONS AND ACCEPTANCE CRITERIA PER FATIGUE TEST PROCEDURES OF MIL-E-1 BASIC SPECIFICATIONS.
4. THESE NORMAL VALUES REPRESENT CONDITIONS AT WHICH CONTROL OF RELIABILITY MAY BE EXPECTED.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

NOTES
CONT'D.

- 5. THESE NORMAL TEST CONDITIONS ARE USED FOR ALL CHARACTERISTICS UNLESS OTHERWISE STATED UNDER THE INDIVIDUAL TEST ITEM.
- 6. FOR MOST APPLICATIONS THE PERFORMANCE WILL NOT BE ADVERSELY AFFECTED BY $\pm 10\%$ HEATER VOLTAGE VARIATION, BUT WHEN THE APPLICATION CAN PROVIDE A CLOSER CONTROL OF HEATER VOLTAGE, AN IMPROVEMENT IN RELIABILITY WILL BE REALIZED.
- 7. PLATE AND SCREEN VOLTAGES SHOULD NOT EXCEED THESE VALUES UNDER ANY CIRCUMSTANCES.
- 8. THE TUBE UNDER TEST SHALL BE RIGIDLY MOUNTED ON A VIBRATION TABLE VIBRATING WITH SIMPLE HARMONIC MOTION. THE TEST CONDITIONS OF PARAGRAPH 4.9.19.1 OF MIL-E-1 SHALL BE APPLIED AND E_p MONITORED WHILE THE FREQUENCY OF VIBRATION IS CONTINUOUSLY SWEEPED FROM 50-3500 CPS AND THE PEAK ACCELERATION CONTROLLED CONSTANT AT 2G. A LOW PASS FILTER WHICH FOLLOWS THE LOAD RESISTOR OF THE TUBE UNDER TEST SHALL HAVE A CUT-OFF FREQUENCY OF 3500 CPS. THE TOTAL TIME OF SWEEP SHALL NOT BE LESS THAN ONE (1) MINUTE.
- 9. TUBES SHALL BE SO SHIELDED THAT OPERATOR PROXIMITY OR MOVEMENT WILL NOT AFFECT OUTPUT READINGS.
- 10. THE REJECTION LEVEL SHALL BE SET AT THE VU METER READING OBTAINED DURING CALIBRATION.

