

20A3

THYRATRON GAS TETRODE

Indirectly heated—for use as Gas Relay

RATING

Heater Voltage (volts)	V_h	6.3
Heater Current (amps)	I_h	0.6
Arc Voltage Drop (volts)		8
Maximum Forward Anode Volts	V_a	650
Maximum Peak Inverse Anode Voltage (volts) P.I.V. (max)		1300
Maximum Shield Grid Voltage (volts)	$V_{g2}(\text{max})$	-100
Maximum Control Grid Volts	$V_{g1}(\text{max})$	-100
Maximum Peak Cathode Current (mA)	$I_k(\text{pk})\text{max}$	500
Maximum Average Cathode Current (mA)	$I_k(\text{av})\text{max}$	100
Control Grid Circuit Res. (Megohms)	R_{g1}	0.01-10.0
Control Ratio G1		250 •
Control Ratio G2		1000 †

$$\bullet \quad V_{g2} = 0 \quad R_{g1} = 0$$

$$\dagger \quad V_{g1} = 0 \quad R_{g1} = 0 \quad R_{g2} = 0$$

IMPORTANT

- 1) Heater to cathode voltage must never exceed 25 volts peak.
- 11) The heater must be switched on for 10 sec min before anode voltage is applied.
- 111) All maximum ratings are absolute values, not design centres.


DIMENSIONS

Overall Length Maximum (mm)	54
Maximum Diameter (mm)	19
Maximum Seated Height (mm)	47.5
Approximate Nett Weight (ozs)	$\frac{1}{2}$
Approximate Packed Weight (ozs)	$\frac{3}{4}$

MOUNTING POSITION - Unrestricted.

20A3**THYRATRON GAS TETRODE**

Indirectly heated—for use as Gas Relay

BASE - Miniature Button 7, pin B7G.

Viewed from free end of pins.

CONNEXIONS

Pin 1	Grid 1	g1
Pin 2	Cathode	k
Pin 3	Heater	h
Pin 4	Heater	h
Pin 5	Grid 2	g2
Pin 6	Anode	a
Pin 7	Grid 2	g2

20A3

THYRATRON GAS TETRODE

Indirectly heated—for use as Gas Relay

AVERAGE CHARACTERISTIC CURVES: V_a/V_g $R_{g1}=0$ $R_{g2}=0$ 