

TUNG-SOL**CATHODE RAY**

THE 21BAP4 IS A DIRECT VIEW PICTURE TUBE DESIGNED FOR TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

ELECTROSTATIC FOCUS	ALUMINIZED SCREEN
MAGNETIC DEFLECTION	GRAY FILTER FACEPLATE
UNIPOTENTIAL CATHODE	19 1/8" X 15" RASTER SIZE
RECTANGULAR GLASS CONSTRUCTION	EXTERNAL CONDUCTIVE COATING
DOES NOT REQUIRE ION TRAP MAGNET	

ELECTRICAL DATA

		ELECTROSTATIC	MAGNETIC
FOCUSING METHOD			
DEFLECTING METHOD			
DEFLECTION ANGLE (APPROX.):			
HORIZONTAL		85	DEGREES
VERTICAL		68	DEGREES
DIAGONAL		90	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):			
CATHODE TO ALL OTHER ELECTRODES		5	$\mu\mu\text{f}$
GRID #1 TO ALL OTHER ELECTRODES		6	$\mu\mu\text{f}$
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE		750	$\mu\mu\text{f}$
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE		500	$\mu\mu\text{f}$

OPTICAL DATA

	SULFIDE TYPE	
PHOSPHOR NUMBER		P-4
FLUORESCENT COLOR		WHITE
PHOSPHORESCENT COLOR		WHITE
PERSISTENCE		SHORT
FACEPLATE TRANSMISSION AT CENTER (APPROX.):	71	PERCENT

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	$0.6 \pm 10\%$	AMP.
MAXIMUM DC ANODE VOLTAGE	20 000	VOLTS
MAXIMUM DC GRID #4 VOLTAGE	-500 TO +1000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	500	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	180	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEGOHMS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE VOLTAGE*	16 000	VOLTS
DC GRID #4 VOLTAGE	0 TO 500	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE^A	-28 TO -72	VOLTS
DC GRID #4 CURRENT	-15 TO +25	μAMP

* BRIGHTNESS AND FOCUS QUALITY DECREASE WITH DECREASING ANODE VOLTAGE. IN GENERAL THE ANODE VOLTAGE SHOULD NOT BE LESS THAN 14,000 VOLTS.

^A VISUAL EXTINCTION OF FOCUSED RASTER.


CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE


MECHANICAL DATA

OVERALL LENGTH	$20 \pm \frac{3}{8}$	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	$21 \frac{3}{8} \pm \frac{1}{8}$	INCHES
WIDTH	$20 \frac{1}{4} \pm \frac{1}{8}$	INCHES
HEIGHT	$16 \frac{3}{8} \pm \frac{1}{8}$	INCHES
MIN. USEFUL SCREEN DIMENSIONS:		
DIAGONAL	$20 \frac{1}{4}$	INCHES
WIDTH	$19 \frac{1}{8}$	INCHES
HEIGHT	15	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J4-21
BASE	SMALL SHELL DUODECAL 6 PIN	B6-63
BASING		12L
BULB CONTACT ALIGNMENT		
J4-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		



PIN 1 - HEATER
 PIN 2 - GRID #1
 PIN 6 - GRID #4
 PIN 10 - GRID #2
 PIN 11 - CATHODE

PIN CONNECTIONS



BOTTOM VIEW

PIN 12 - HEATER
 ANODE CAP:
 GRID NO. 3
 GRID NO. 5