

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
110° MAGNETIC DEFLECTION

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater Current at 6.3 volts.	450 ± 5%	ma
Heater Warm-Up Time (Average).	11	seconds
Direct Interelectrode Capacitances:		
Grid No.1 to all other electrodes.	6	μμf
Cathode to all other electrodes.	5	μμf
External conductive coating to ultor	{ 2500 max. 1700 min.	{ μμf μμf
Electron Gun	Type Requiring No Ion-Trap Magnet	

Optical:

Faceplate.	Filterglass
Light transmission (Approx.)	76%
Phosphor (For curves, see front of this section)	P4—Sulfide Type, Aluminized

Mechanical:

Operating Position	.Any
Weight (Approx.)	20 lbs
Overall Length	14-11/16" + 5/16" - 5/8"
Neck Length.	5-7/16" + 1/8" - 7/16"
Projected Area of Screen	262 sq. in.
External Conductive Coating:	

Type	Regular Band
Contact area for grounding	Near Reference Line

For Additional Information on Coatings and Dimensions:

See *Picture-Tube Dimensional-Outlines* and *Bulb J171 C/K* sheets at the front of this section

Cap. Recessed Small Cavity (JEDEC No.J1-21)


Bases (Alternates):

Small-Button Eightar 7-Pin, Arrangement 2,
(JEDEC No.B7-183)

Small-Button Neoeightar 7-Pin, Arrangement 1,
(JEDEC No.B7-208)

Basing Designation for BOTTOM VIEW 8HR

Pin 1—Heater
Pin 2—Grid No.1
Pin 3—Grid No.2
Pin 4—Grid No.4
Pin 6—Grid No.1
Pin 7—Cathode
Pin 8—Heater



Cap—Ultor
(Grid No.3,
Grid No.5,
Collector)
C—External
Conductive
Coating



21DHP4

Maximum Ratings, Design-Maximum Values:

ULTOR VOLTAGE.	19800 max.	volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value	1100 max.	volts
Negative value	550 max.	volts
GRID-No.2 VOLTAGE.	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value.	220 max.	volts
Negative bias value.	154 max.	volts
Positive bias value.	0 max.	volts
Positive peak value.	2 max.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds	450 max.	volts
After equipment warm-up period . . .	200 max.	volts
Heater positive with respect to cathode	200 max.	volts

Typical Operating Conditions:

With ultor voltage of	16000	volts
and grid-No.2 voltage of	300	volts
Grid-No.4 Voltage for focus.	0 to 400	volts
Grid-No.1 Voltage for visual extinction of focused raster.	-35 to -72	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance	1.5 max.	megohms
--	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section