

EDISWAN

21N15

MERCURY VAPOUR THYRATRON

Indirectly heated

21N15

GENERAL

The 21N15 is a Mercury Vapour Thyatron suitable for welding and motor control. It has an indirectly heated oxide coated cathode.

RATING

Heater Voltage	V_h	5.0	V
Heater Current	I_h	5.0	A
Maximum Peak Forward Anode Voltage		1.5	kV
Maximum Peak Inverse Anode Voltage	P.I.V.(max)	1.25	kV
Maximum Negative Grid Voltage (before Conduction)		500	V
Maximum Negative Grid Voltage (during Conduction)		10	V
Maximum Mean Cathode Current (maximum averaging 15 seconds)	$I_{k(av)max}$	3.0	A
Maximum Peak Cathode Current (25c/s and above)	$i_{k(pk)max}$	20	A
Maximum Surge Cathode Current (Fault protection maximum duration 0.1 seconds)		200	A
Maximum Critical Grid Current (at $V_a = 1.0kV$)		<10	μA
Maximum Power Supply Frequency		150	c/s
Condensed Mercury Temperature Limits	T_{Hg}	40 to 75	$^{\circ}C$
Control Ratio		150:1	
De-ionisation Time (approx)		1,000	μs
Ionisation Time (approx)		10	μs
Anode Voltage Drop		16	V
Maximum Grid Resistance	$R_g(max)$	100	$k\Omega$
Recommended Minimum Grid Resistance	$R_g(min)$	10	$k\Omega$

May, 1961

ADVANCE DATA

Associated Electrical Industries Limited

RADIO & ELECTRONIC COMPONENTS DIVISION

2IN15

EDISWAN

2IN15

MERCURY VAPOUR THYRATRON

Indirectly heated


DIMENSIONS

Maximum Overall Length	199 mm
Maximum Diameter	57 mm
Maximum Seated Height	184 mm

MOUNTING POSITION—Vertical, Base down

CAP—CT3

BASE—UX4 (E.I.A. No. A4-10)



Viewed from free end of pins.

CONNECTIONS

Pin 1	Heater	h
Pin 2	Heater, Cathode	h, k
Pin 3	Grid	g
Pin 4	Heater, Cathode	h, k
Cap	Anode	a

May, 1961

ADVANCE DATA

Associated Electrical Industries Limited

RADIO & ELECTRONIC COMPONENTS DIVISION