

TUNG-SOL

CATHODE RAY

THE 21XP4 AND 21XP4A ARE DIRECT-VIEW PICTURE TUBES INTENDED FOR TELEVISION APPLICATIONS. THEY ARE IDENTICAL *EXCEPT* FOR THE ALUMINIZED SCREEN ON THE 21XP4A. THEIR COMMON FEATURES INCLUDE:

MAGNETIC DEFLECTION	SPHERICAL FACEPLATE
UNIPOENTIAL CATHODE	GREY FILTER FACEPLATE
RECTANGULAR GLASS CONSTRUCTION	EXTERNAL CONDUCTIVE COATING
LOW VOLTAGE ELECTROSTATIC FOCUS	EXTERNAL SINGLE FIELD ION TRAP

12 3/4" X 17" RASTER SIZE

ELECTRICAL DATA

FOCUSING METHOD	LOW VOLTAGE ELECTROSTATIC	
DEFLECTING METHOD	MAGNETIC	
DEFLECTION ANGLE (APPROX.):		
HORIZONTAL	66	DEGREES
VERTICAL	50	DEGREES
DIAGONAL	70	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	μlf
GRID #1 TO ALL OTHER ELECTRODES	6	μlf
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	750	μlf
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	500	μlf

OPTICAL DATA


PHOSPHOR NUMBER	P-4
FLUORESCENT COLOR	WHITE
PHOSPHORESCENT COLOR	WHITE
PERSISTENCE	MEDIUM
FACEPLATE LIGHT TRANSMISSION AT CENTER (APPROX.)	72 PERCENT

MECHANICAL DATA

OVERALL LENGTH	22 7/16 $\pm$ 3/8	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	20 5/8 $\pm$ 3/16	INCHES
WIDTH	18 11/16 $\pm$ 1/8	INCHES
HEIGHT	14 15/16 $\pm$ 1/8	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS:		
WIDTH	17	INCHES
HEIGHT	12 3/4	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J1-21
BASE	SMALL SHELL DUODECAL 6 PIN	B6-63
BASING		12L
BULB CONTACT ALIGNMENT		
J1-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		

PIN CONNECTIONS

PIN 1 - HEATER
PIN 2 - GRID NO. 1
PIN 6 - GRID NO. 4
PIN 10 - GRID NO. 2
PIN 11 - CATHODE



BOTTOM VIEW

PIN 12 - HEATER
ANODE CAP:
GRID NO. 3
GRID NO. 5

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS

DESIGN CENTER VALUES

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC ANODE, GRID #3 GRID #5 VOLTAGE	18 000	VOLTS
MAXIMUM DC GRID #4 VOLTAGE (FOCUSING ELECTRODE)	-500 TO +1000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	500	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	180	VOLTS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE, GRID #3, GRID #5 VOLTAGE	16 000	VOLTS
DC GRID #4 VOLTAGE (FOCUSING ELECTRODE) ^A	-64 TO +352	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^B	-28 TO -72	VOLTS
DC ION TRAP CURRENT STANDARD COIL #117 (APPROX.)	30 ± 40%	MA.
ION TRAP MAGNET FIELD STRENGTH (APPROX.)	35	GAUSSSES

^A WITH THE COMBINED GRID #1 BIAS VOLTAGE AND VIDEO-SIGNAL VOLTAGE ADJUSTED TO GIVE AN ANODE CURRENT OF 100 MICROAMPERES ON A 12 3/4" X 17" PICTURE SIZE.

^B VISUAL EXTINCTION OF FOCUSED RASTER.

CIRCUIT VALUES

MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEGOHMS
------------------------------------	-----	---------

TUNG-SOL

