

TUNG-SOL

CATHODE RAY

THE 22AP4 AND 22AP4A ARE DIRECT-VIEW PICTURE TUBES DESIGNED FOR USE IN TELEVISION APPLICATIONS. THEY ARE IDENTICAL *EXCEPT* THAT THE 22AP4 HAS A GREY FILTER FACEPLATE. THEIR COMMON FEATURES INCLUDE:

UNIPOTENTIAL CATHODE	ROUND METAL CONSTRUCTION
MAGNETIC FOCUS AND DEFLECTION	EXTERNAL SINGLE FIELD ION TRAP
13 1/2" X 18" RASTER SIZE	

ELECTRICAL DATA

FOCUSING METHOD		MAGNETIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.)	70	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	$\mu\mu\text{f}$
GRID #1 TO ALL OTHER ELECTRODES	6	$\mu\mu\text{f}$

OPTICAL DATA


PHOSPHOR NUMBER	NO. 4
FLUORESCENT COLOR	WHITE
PHOSPHORESCENT COLOR	WHITE
PERSISTENCE	MEDIUM
FACEPLATE LIGHT TRANSMISSION AT CENTER (APPROX.)	22AP4A 66 PERCENT

MECHANICAL DATA

OVERALL LENGTH	22 7/8 $\pm$ 1/2	INCHES
GREATEST DIAMETER OF BULB	21 11/16 $\pm$ 1/8	INCHES
MINIMUM USEFUL SCREEN DIAMETER	20 1/4	INCHES
BULB CONTACT	METAL SHELL LIP	
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		120

PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID NO. 1
 PIN 10 - GRID NO. 2
 PIN 11 - CATHODE



PIN 12 - HEATER
 METAL SHELL LIP:
 ANODE
 GRID NO. 3

BOTTOM VIEW

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS

DESIGN CENTER VALUES

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC GRID #2 VOLTAGE	410	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE ^A :		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	140	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	140	VOLTS

^A THE CATHODE SHOULD BE RETURNED TO ONE SIDE OR TO THE MID-TAP OF THE HEATER TRANSFORMER WINDING.

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE, GRID #3 VOLTAGE	14 000	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^B	-33 TO -77	VOLTS
DC FOCUSING COIL CURRENT ^C (APPROX.)	117	MA.
ION TRAP MAGNET (RATED STRENGTH) APPROX.	35	GAUSSSES

^B FOR VISUAL EXTINCTION OF UNDEFLECTED FOCUSED SPOT.

^C FOR STANDARD FOCUS COIL #109, OR EQUIVALENT, WITH THE COMBINED GRID #1 BIAS VOLTAGE AND VIDEO SIGNAL VOLTAGE ADJUSTED TO PRODUCE A HIGHLIGHT BRIGHTNESS OF 25 FOOT LAMBERTS ON A 18" BY 13 1/2" PICTURE SIZE. DISTANCE FROM REFERENCE LINE TO CENTER OF AIR GAP ON FOCUS COIL SHALL BE 3.0 INCHES.

CIRCUIT VALUES

MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEGOHMS
------------------------------------	-----	---------

TUNG-SOL

