

TUNG-SOL**CATHODE RAY**

THE 24ADP4 IS A DIRECT VIEW PICTURE TUBE DESIGNED FOR TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

GRAY FILTER FACEPLATE	ALUMINIZED SCREEN
MAGNETIC FOCUS AND DEFLECTION	UNIPOTENTIAL CATHODE
RECTANGULAR GLASS CONSTRUCTION	EXTERNAL CONDUCTIVE COATING
21 7/16" X 16 7/8" RASTER SIZE	EXTERNAL SINGLE FIELD ION TRAP

ELECTRICAL DATA

FOCUSING METHOD		
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.)		MAGNETIC
HORIZONTAL	85	DEGREES
DIAGONAL	90	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	μf
GRID #1 TO ALL OTHER ELECTRODES	6	μf
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	2500	μf
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	2000	μf

OPTICAL DATA

PHOSPHOR NUMBER	SULFIDE TYPE	P-4
FLUORESCENT COLOR		WHITE
PHOSPHORESCENT COLOR		WHITE
PERSISTENCE	SHORT TO MEDIUM	
FACEPLATE TRANSMISSION AT CENTER (APPROX.):	75	PERCENT

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6 $\pm 5\%$	AMP.
MAXIMUM DC ANODE VOLTAGE	24 200	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	660	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	155	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 45 SECONDS	450	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	200	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEG OHMS
HEATER WARM-UP TIME (APPROX.)*	11.0	SECONDS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE VOLTAGE	18 000	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^A	-28 TO -72	VOLTS
DC FOCUSING COIL CURRENT (APPROX.)	125 $\pm 15\%$	MA.
DC ION TRAP MAGNET STANDARD COIL #117 (APPROX.)	32	MA.
DC ION TRAP MAGNET RATED STRENGTH	36	GAUSSSES

^A VISUAL EXTINGUISH OF FOCUSED RASTER.

* HEATER WARM-UP TIME IS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TERMINALS TO INCREASE TO 5.0 VOLTS IN THE JETEC TEST CIRCUIT, WITH $E=25$ VOLTS AND SERIES $R=31.5$ OHMS.


CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE


MECHANICAL DATA

OVERALL LENGTH	21 $\frac{1}{8}$ $\pm$ $\frac{3}{8}$	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	24 $\pm$ $\frac{1}{8}$	INCHES
WIDTH	22 $\frac{11}{16}$ $\pm$ $\frac{1}{8}$	INCHES
HEIGHT	18 $\frac{7}{16}$ $\pm$ $\frac{1}{8}$	INCHES
MIN. USEFUL SCREEN DIMENSIONS:		
DIAGONAL	22 $\frac{11}{16}$	INCHES
WIDTH	21 $\frac{7}{16}$	INCHES
HEIGHT	18 $\frac{7}{16}$	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J4-21
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		12N
BULB CONTACT ALIGNMENT		
J4-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		



PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID #1
 PIN 10 - GRID #2
 PIN 11 - CATHODE



PIN 12 - HEATER
 ANODE CAP:
 GRID NO. 3

BOTTOM VIEW