

TUNG-SOL

CATHODE RAY

THE 24TP4 IS A DIRECT-VIEW PICTURE TUBE DESIGNED FOR USE IN TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

SPHERICAL FACEPLATE	UNIPOTENTIAL CATHODE
ALUMINIZED FACEPLATE	GREY FILTER FACEPLATE
MAGNETIC FOCUS & DEFLECTION	EXTERNAL CONDUCTIVE COATING
RECTANGULAR GLASS CONSTRUCTION	EXTERNAL SINGLE FIELD ION TRAP

ELECTRICAL DATA

FOCUSING METHOD		
DEFLECTING METHOD		
DEFLECTING ANGLE (APPROX.) DIAGONAL	90	MAGNETIC MAGNETIC DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	$\mu\mu f$
GRID #1 TO ALL OTHER ELECTRODES	6	$\mu\mu f$
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	750	$\mu\mu f$
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	250	$\mu\mu f$


OPTICAL DATA

PHOSPHOR NUMBER		NO. 4
FLUORESCENT COLOR		WHITE
PHOSPHORESCENT COLOR		WHITE
PERSISTENCE		MEDIUM
FACEPLATE LIGHT TRANSMISSION AT CENTER (APPROX.)	72	PERCENT

MECHANICAL DATA

OVERALL LENGTH	$21 \frac{1}{8} \pm \frac{3}{8}$	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	24	INCHES
WIDTH	$22 \frac{11}{16}$	INCHES
HEIGHT	$18 \frac{7}{16}$	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS:		
WIDTH	$21 \frac{7}{16}$	INCHES
HEIGHT	$17 \frac{1}{8}$	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J4-21
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		12N

PIN CONNECTIONS



PIN 1 - HEATER
PIN 2 - GRID NO. 1
PIN 10 - GRID NO. 2

PIN 11 - CATHODE
PIN 12 - HEATER
ANODE CAP

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS

DESIGN CENTER VALUES

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC ANODE VOLTAGE	20 000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	500	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	180	VOLTS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE VOLTAGE	14 000	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^A	-33 TO -77	VOLTS
DC FOCUSING COIL CURRENT ^B (APPROX.)	110 ± 10	MA.
DC ION TRAP CURRENT STANDARD COIL #111 (APPROX.)	85 ± 50%	MA.

^A VISUAL EXTINCTION OF UNDEFLECTED FOCUSED SPOT.^B FOR STANDARD FOCUS COIL #109.

CIRCUIT VALUES

MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEG OHMS
------------------------------------	-----	----------

TUNG-SOL

