

TUNG-SOL**CATHODE RAY**

THE 27LP4 IS A DIRECT-VIEW PICTURE TUBE DESIGNED FOR USE IN TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

GREY FILTER FACEPLATE	ALUMINIZED SCREEN
EXTERNAL CONDUCTIVE COATING	UNIPOTENTIAL CATHODE
MAGNETIC FOCUS AND DEFLECTION	EXTERNAL SINGLE FIELD ION TRAP
RECTANGULAR GLASS CONSTRUCTION	18 15/32" X 23 17/32" RASTER SIZE

ELECTRICAL DATA

FOCUSING METHOD		MAGNETIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.):		
HORIZONTAL	85	DEGREES
DIAGONAL	90	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	μf
GRID #1 TO ALL OTHER ELECTRODES	6	μf
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	400	μf
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	250	μf

OPTICAL DATA


PHOSPHOR NUMBER	NO. 4
FLUORESCENT COLOR	WHITE
PHOSPHORESCENT COLOR	WHITE
PERSISTENCE	MEDIUM

MECHANICAL DATA

OVERALL LENGTH	24 23/64 $\pm$ 3/8	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	26 13/16 $\pm$ 1/4	INCHES
WIDTH	25 9/32 $\pm$ 1/4	INCHES
HEIGHT	20 7/32 $\pm$ 1/4	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS:		
WIDTH	23 17/32	INCHES
HEIGHT	18 15/32	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J1-21
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		12N
BULB CONTACT ALIGNMENT		
J1-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		

PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID NO. 1
 PIN 10 - GRID NO. 2
 PIN 11 - CATHODE



PIN 12 - HEATER
 ANODE CAP:
 GRID NO. 3

BOTTOM VIEW

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CATHODE RAY

THE 27LP4 IS A DIRECT-VIEW PICTURE TUBE DESIGNED FOR USE IN TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

GREY FILTER FACEPLATE	ALUMINIZED SCREEN
EXTERNAL CONDUCTIVE COATING	UNIPOTENTIAL CATHODE
MAGNETIC FOCUS AND DEFLECTION	EXTERNAL SINGLE FIELD ION TRAP
RECTANGULAR GLASS CONSTRUCTION	18 15/32" X 23 17/32" RASTER SIZE

ELECTRICAL DATA

FOCUSING METHOD		MAGNETIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.):		
HORIZONTAL	85	DEGREES
DIAGONAL	90	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.):		
CATHODE TO ALL OTHER ELECTRODES	5	μf
GRID #1 TO ALL OTHER ELECTRODES	6	μf
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	400	μf
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	250	μf

OPTICAL DATA


PHOSPHOR NUMBER	NO. 4
FLUORESCENT COLOR	WHITE
PHOSPHORESCENT COLOR	WHITE
PERSISTENCE	MEDIUM

MECHANICAL DATA

OVERALL LENGTH	24 23/64 $\pm$ 3/8	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	26 13/16 $\pm$ 1/4	INCHES
WIDTH	25 9/32 $\pm$ 1/4	INCHES
HEIGHT	20 7/32 $\pm$ 1/4	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS:		
WIDTH	23 17/32	INCHES
HEIGHT	18 15/32	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J1-21
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		12N
BULB CONTACT ALIGNMENT		
J1-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		

PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID NO. 1
 PIN 10 - GRID NO. 2
 PIN 11 - CATHODE



PIN 12 - HEATER
 ANODE CAP:
 GRID NO. 3

BOTTOM VIEW

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

