

TUNG-SOL**CATHODE RAY**

THE 27SP4 IS A DIRECT-VIEW PICTURE TUBE DESIGNED FOR USE IN TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

ALUMINIZED SCREEN	SPHERICAL FACEPLATE
UNIPOTENTIAL CATHODE	MAGNETIC DEFLECTION
EXTERNAL CONDUCTIVE COATING	GREY FILTER FACEPLATE
RECTANGULAR GLASS CONSTRUCTION	24" X 18 1/2" RASTER SIZE
LOW VOLTAGE ELECTROSTATIC FOCUS	EXTERNAL SINGLE FIELD ION TRAP

ELECTRICAL DATA

FOCUSING METHOD	LOW VOLTAGE ELECTROSTATIC
DEFLECTING METHOD	MAGNETIC
DEFLECTION ANGLE: (APPROX.)	
HORIZONTAL	85 DEGREES
DIAGONAL	90 DEGREES
DIRECT INTERELECTRODE CAPACITANCES: (APPROX.)	
CATHODE TO ALL OTHER ELECTRODES	5 μ f
GRID #1 TO ALL OTHER ELECTRODES	6 μ f
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE ^A	750 μ f
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE ^A	500 μ f

^A EXTERNAL CONDUCTIVE COATING MUST BE GROUNDING.

OPTICAL DATA


PHOSPHOR NUMBER	P-4
FLUORESCENT COLOR	WHITE
PHOSPHORESCENT COLOR	WHITE
PERSISTENCE	MEDIUM
FACEPLATE LIGHT TRANSMISSION AT CENTER (APPROX.)	68 PERCENT

MECHANICAL DATA

OVERALL LENGTH	23 1/16 $\pm$ 3/8	INCHES
GREATEST DIMENSIONS OF BULB:		
DIAGONAL	26 13/16	INCHES
WIDTH	25 9/32 $\pm$ 3/16	INCHES
HEIGHT	20 7/32 $\pm$ 3/16	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS:		
WIDTH	24	INCHES
HEIGHT	18 1/2	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J1-21
BASE	SMALL SHELL DUODECAL 6 PIN	86-63
BASING		12L
BULB CONTACT ALIGNMENT		
J1-21 CONTACT ALIGNS WITH PIN POSITION #6 $\pm$ 30 DEGREES		

PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID NO. 1
 PIN 6 - GRID NO. 4
 PIN 10 - GRID NO. 2
 PIN 11 - CATHODE



PIN 12 - HEATER
 ANODE CAP:
 GRID NO. 3
 GRID NO. 5

BOTTOM VIEW

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS

DESIGN CENTER VALUES

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC ANODE, GRID #3, GRID #5 VOLTAGE	20 000	VOLTS
MAXIMUM DC GRID #4 VOLTAGE (FOCUSING ELECTRODE)	-500 TO +1000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	500	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	180	VOLTS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE, GRID #3, GRID #5 VOLTAGE ^B	18 000	VOLTS
DC GRID #4 VOLTAGE (FOCUSING ELECTRODE)	-72 TO +396	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE REQUIRED FOR CUTOFF ^C	-28 TO -72	VOLTS
ION TRAP MAGNET STRENGTH (APPROX.)	40	GAUSSSES

^B BRILLIANCE AND DEFINITION DECREASE WITH DECREASING ANODE VOLTAGE. IN GENERAL, ANODE VOLTAGE SHOULD NOT BE LESS THAN THIS VALUE.

^C VISUAL EXTINCTION OF FOCUSED RASTER. EXTINCTION OF THE STATIONARY FOCUSED SPOT WILL REQUIRE THAT THESE VALUES BE ABOUT 5 VOLTS MORE NEGATIVE.

CIRCUIT VALUES

MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEGOHMS
------------------------------------	-----	---------

TUNG-SOL

