



DESCRIPTION AND RATING

FOR GROUNDED-GRID OSCILLATOR AND AMPLIFIER SERVICE

Metal and Ceramic Low Interelectrode Capacitances
 High Transconductance Shock Resistant

100 Watts Plate Dissipation

The 2C39-B is a metal-and-ceramic, high- μ triode designed for use as a grounded-grid oscillator or amplifier at frequencies as high as 2500 megacycles.

Features of the 2C39-B include planar electrode construction, high plate dissipation capability, excellent electrode isolation, low radio-frequency losses, high transconductance, and low interelectrode capacitances.

GENERAL

ELECTRICAL

Cathode—Coated Unipotential
 Heater Characteristics and Ratings
 Heater Voltage, AC or DC * Volts
 Heater Current at $E_f = 6.3$ volts 1.03† Amperes
 Direct Interelectrode Capacitances‡
 Grid to Plate: (g to p) 2.01 pf
 Grid to Cathode: (g to k) 6.5 pf
 Plate to Cathode: (p to k) 0.023 pf

MECHANICAL

Mounting Position—Any—Only Plate Flange to Be Used as a Socket Stop and Clamp
 Net Weight, approximate 2 Ounces
 Cooling
 Plate and Plate Seal—Conduction and Forced Air
 Grid and Cathode Seals—Conduction and Forced Air
 Recommended Air Flow Cowling—157-JAN
 Recommended Air Flow on Plate Radiator at Sea Level
 Incoming Air Temperature 25C, Plate Dissipation
 100 Watts 12.5 Cubic Feet Per Minute

MAXIMUM RATINGS

ABSOLUTE-MAXIMUM VALUES

RADIO-FREQUENCY POWER AMPLIFIER AND OSCILLATOR—CLASS C TELEGRAPHY

Key-Down Conditions per Tube Without Amplitude Modulation§
 Heater Voltage* 4.5 to 6.3 Volts
 DC Plate Voltage 1000 Volts
 Negative DC Grid Voltage 150 Volts
 Peak Positive RF Grid Voltage 30 Volts
 Peak Negative RF Grid Voltage 400 Volts
 DC Grid Current 50 Milliampères
 DC Cathode Current 125 Milliampères
 Plate Dissipation 100 Watts
 Grid Dissipation 2.0 Watts
 Envelope Temperature at Hottest Point ¶ 250 C

RADIO-FREQUENCY POWER AMPLIFIER AND OSCILLATOR—CLASS C TELEPHONY

Carrier Conditions per Tube For Use With a Maximum Modulation Factor of 1.0
 Heater Voltage* 4.5 to 6.3 Volts
 DC Plate Voltage¶ 600 Volts
 Negative DC Grid Voltage 150 Volts
 Peak Positive RF Grid Voltage 30 Volts
 Peak Negative RF Grid Voltage 400 Volts
 DC Grid Current 50 Milliampères
 DC Cathode Current 100 Milliampères
 Plate Dissipation 70 Watts
 Grid Dissipation 2.0 Watts
 Envelope Temperature at Hottest Point ¶ 250 C

CHARACTERISTICS AND TYPICAL OPERATION

AVERAGE CHARACTERISTICS

Heater Voltage.....	6.3	Volts
Plate Voltage.....	600	Volts
Grid Voltage△.....		Volts
Amplification Factor.....	95	
Transconductance.....	24800	Micromhos
Plate Current.....	75	Milliamperes

* The equipment designer should design the equipment so that heater voltage is centered at some value within the range of 4.5 to 6.3 volts. Heater voltage variations about the center value should be kept as small as practical and should not, in any case, exceed $\pm 5\%$. The optimum center value of heater voltage depends on the cathode current and on other parameters of circuit design and operation. For specific recommendations, contact your General Electric tube sales representative.

† Heater current of a bogey tube at Ef = 6.3 volts.

RADIO FREQUENCY OSCILLATOR—CLASS C

Frequency.....	500	2500	Megacycles
Heater Voltage.....	6.0	5.0	Volts
DC Plate Voltage.....	900	900	Volts
DC Plate Current.....	90	90	Milliamperes
DC Grid Current.....	30	27	Milliamperes
DC Grid Voltage.....	-40	-22	Volts
Useful Power Output.....	40	17	Watts

‡ Measured in a special shielded socket.

§ Modulation essentially negative may be used if the positive peak of the audio-frequency envelope does not exceed 115 percent of the carrier conditions.

* Where long life and reliable operation are important, lower envelope temperatures should be used.

¶ For modulation factors less than 1.0, a higher d-c plate voltage may be used if the sum of the peak positive audio voltage and the d-c plate voltage does not exceed 1200 volts.

△ Adjusted for Ib = 75 milliamperes.

INITIAL CHARACTERISTICS LIMITS

	Min.	Bogey	Max.	
Heater Current				
Ef = 6.3 volts.....	950	1030	1100	Milliamperes
Grid Voltage				
Ef = 6.3 volts, Eb = 600 volts, Ib = 75 ma.....	-1.3	-2.5	-3.5	Volts
Grid Voltage				
Ef = 6.3 volts, Eb = 600 volts, Ib = 1.0 ma.....	-7.0	-9.5	-15	Volts
Transconductance				
Ef = 6.3 volts, Eb = 600 volts, Ec adjusted for Ib = 75 ma.....	22000	24800	27500	Micromhos
Amplification Factor				
Ef = 6.3 volts, Eb = 600 volts, Ec adjusted for Ib = 75 ma.....	75	95	115	
Negative Grid Current				
Ef = 6.3 volts, Eb = 600 volts, Ec adjusted for Ib = 75 ma.....			3.0	Microamperes
Interelectrode Leakage Resistance				
Ef = 6.3 volts, Polarity of applied d-c interelectrode voltage is such that no cathode emission results				
Grid to Cathode at 500 volts d-c.....	50			Megohms
Interelectrode Capacitances				
Grid to Plate: (g to p).....	1.89	2.01	2.13	Picofarads
Grid to Cathode: (g to k).....	6.0	6.5	7.0	Picofarads
Plate to Cathode: (p to k).....	0.018	0.023	0.029	Picofarads

Absolute-Maximum ratings are limiting values of operating and environmental conditions applicable to any electron tube of a specified type as defined by its published data and should not be exceeded under the worst probable conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube, making no allowance for equipment variations, environmental variations, and the effects of changes in operating conditions due to variations in the characteristics of the tube under consideration and of


all other electron devices in the equipment.

The equipment manufacturer should design so that initially and throughout life no absolute-maximum value for the intended service is exceeded with any tube under the worst probable operating conditions with respect to supply-voltage variation, equipment component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in the characteristics of the tube under consideration and of all other electron devices in the equipment.


The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or

elements. In the absence of an express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.


AVERAGE PLATE CHARACTERISTICS




AVERAGE PLATE CHARACTERISTICS



AVERAGE CONSTANT-CURRENT CHARACTERISTICS



AVERAGE CONSTANT-CURRENT CHARACTERISTICS



RECEIVING TUBE DEPARTMENT

GENERAL  **ELECTRIC**

Owensboro, Kentucky