



RADIO MANUFACTURERS ASSOCIATION
ENGINEERING DEPARTMENT

Release No. 443

October 5, 1945

sponsor:
Sperry Gyroscope Co., Inc.

Type 2K31
Velocity Modulation Amplifier/Oscillator

General Characteristics

Electrical

Cathode	Indirectly Heated
Heater Voltage (A.C. or D.C.)	6.3 volts
Heater Current	1.3 amperes

Tentative Maximum Ratings

Acceleration Voltage	2000 volts
Beam Current	60 milliamperes
Control Grid Voltage	50 volts (positive)
Control Grid Current	25 milliamperes
Beam Power Input	100 watts
Forced air cooling should be used for beam power inputs exceeding 20 watts	

Typical Operation

Acceleration Voltage	430 volts	1800 volts
Beam Current	20 milliamperes	50 milliamperes
Output	30-75 milliwatts	3 watts
Load Resistance	70 ohms.	
Tuning Range	9.0 cm to 11.0 cm	

Mechanical

Maximum Overall Height	5 1/4 inches
Tube Body Diameter	1 3/4 inches
Maximum Diameter	3 1/16 inches
Envelope	special construction metal and glass
Base	intermediate shell octal 8 pin
Base Connection	see outline drawing
Permissible Mounting Position	any
Approximate Weight	11 ounces



RADIO MANUFACTURERS ASSOCIATION
ENGINEERING DEPARTMENT

Release No. 443

October 5, 1945

RMA TYPE 2K31
(Continued)

