



2X2-A

2X2-A

HALF-WAVE VACUUM RECTIFIER*For applications critical as to severe shock and vibration***GENERAL DATA****Electrical:**


Heater, for Unipotential Cathode:

	Min.	Av.	Max.	
Voltage.	2.25	2.50	2.75	ac volts
Current at 2.50 volts. . .	1.55	1.75	1.95	amp

Mechanical:

Mounting Position.	Any
Maximum Overall Length	4-17/32" ←
Seated Length.	3-25/32" ± 1/8"
Maximum Diameter	1-9/16"
Dimensional Outline.	See General Section
Weight (Approx.)	1.3 oz ←
Eulb	ST-12
Cap.	Small (JETEC No.C1-1) ←
Base	Small-Shell Small 4-Pin (JETEC No.A4-5) ←
Basing Designation for BOTTOM VIEW	4AB

Pin 1 - Heater
 Pin 2 - No Connection
 Pin 3 - No Connection



Pin 4 - Heater,
 Cathode
 Cap - Plate

HALF-WAVE RECTIFIER**Maximum Ratings, Design-Center Values:**

PEAK INVERSE PLATE VOLTAGE	12500 max.	volts
PEAK PLATE CURRENT	60 max.	ma
DC OUTPUT CURRENT.	7.5 max.	ma
HOT-SWITCHING TRANSIENT CURRENT, for duration of 0.2 second max.	100 max.	ma
AMBIENT TEMPERATURE.	70 max.	oC ←

Typical Operation:

AC Plate-Supply Voltage (RMS).	5500	volts
Total Effective Plate-Supply Impedance . .	0.3	megohm
Filter Input Capacitor	0.1	μf
DC Output Current.	2	ma
DC Output Voltage (At input to filter) . .	4500	volts

SHOCK TEST DATA

Impact Acceleration.	250 max.	g
------------------------------	----------	---

This test is performed on a sample lot of tubes from each production run to determine ability of tube to withstand the specified impact acceleration. The tubes are subjected to a total of 3 blows in each of the 3 primary mutually

← indicates a change.

SEPT. 1, 1955

TUBE DIVISION

DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

2X2-A



2X2-A

HALF-WAVE VACUUM RECTIFIER

perpendicular tube planes when tested in the Navy Type, High-Impact (flyweight) Shock Machine. At the end of this test, tubes will not show permanent or temporary shorts or open circuits, and will not be inoperative.

